
OIL FIRED BURNER PRODUCTS & SPARES GUIDE







ABGO offer a nationwide mail order service supplying Oil & Gas Heating & Range Cooker spares to the trade. Our highly experienced technical sales staff are available to assist you with all of your requirements.

We provide a first class, prompt and reliable service from a wide and varied stockholding geared towards our customers' needs.

This guide has been produced to help assist the Heating Professional, and is based on manufacturers information that we believe to be accurate, however ABGO cannot accept responsibility for incorrect part selection. E & OE. Please see our Terms & Conditions of sale, available upon request.

PLEASE CALL US FOR YOUR SPECIFIC BUYING PRICES, WE GIVE OUR BEST PRICES TO HEATING ENGINEERS

The products in this guide are our normally stocked products and are the main serviceable parts which are commonly replaced, please contact us for other items in the range not shown.

We also have many other brands available, please see list below.

ABGO are committed to supporting Heating Engineers.

The pressure of modern business life can cause the little everyday courtesies to be forgotten. At ABGO, we would like you to know that we appreciate your business and thank you for giving us the opportunity of being of service.

RETURNS

In the unfortunate instance that you receive faulty or damaged goods please contact the ABGO sales office for a returns number. Please have the Invoice number to which the goods were supplied on when contacting us, with the fault that you believe to be on the component, this must be stated on the return forms in order for the manufacturer to investigate.

Goods can no longer be returned under any circumstances without ABGO returns paperwork included with returned goods. Goods ordered incorrectly must be returned within 7 days of purchase.

Handling charges will apply and the goods must be in a re-saleable condition. We are unable to accept any unwanted Electronic/PCB goods where the security-seal has been broken.

ABGO is part of

UKE UK Electric

DELIVERIES



Small Parcels - Under 1kg & fit inside express box

Excludes fragile objects, eg. glass, ceramic,

insulation, radiants, coals etc

£4.50 48hr Tracked

Available until 3:30pm

Premium Parcels - Under 25kg



£8.95 Next working day ★ Free over £175 nett ★

£10.95 Before 12:00 next working day

£19.95 Before 10:30 next working day

£19.95 Saturday delivery

£25.00 Saturday before 12:00

£15.95 Offshore & Highlands (2-3 days)

Available until 5:00pm



Pallets

Rates on application
Typically from £48.00

Available until 1:00pm



CONTENTS

OIL BURNERS					
RIELLO BURNERS	6	ECOFLAM BURNERS	7	NU-WAY BURNERS	8
EOGB BURNERS	9	EGGI E/ WI BOTH VEITO		NO WIL BOTHLETO	
OIL BURNER SPARES					
DANFOSS PUMPS	12-14	RIELLO PUMPS	15	SUNTEC & DELTA PUN	MPS 16
AIR ADJUSTMENT	17	DRIVE COUPLINGS	18-19	MOTORS	20-21
CAPACITORS	22-23	FAN WHEELS	24-25	ELECTRODES	26-27
HT LEADS	28-29	TRANSFORMERS	30	CONTROL BOXES	32-33
PHOTOCELLS	34-35	BLAST TUBES	36-38	NOZZLE HOLDERS	39
MOUNTING GASKETS	40-41	NOZZLES	42-44		
OIL SUPPLY SPARES					
FLEXIBLE OIL LINES	46	NIPPLES & VALVES	47	FILTERS	48-50
SOS TANK KITS	52-53	OCV'S & SOLENOIDS	54	DE-AERATORS	55
FIRE VALVES	56-57	TANK ACCESSORIES	58-61	OIL LIFTERS	62
WATCHMAN TANK GAUGES	63	FITTINGS	64-65	OIL TANKS	66
ADDITIVES & METERS	67				
OIL DOLLED CDADEC					
OIL BOILER SPARES					
FIREBIRD	70-74	GAH	75	GRANT	76-83
WARMFLOW	84-85	TRIANCO	86-88	WORCESTER	89-93
GRANDEE	94	POTTERTON	95	HRM	96
MISTRAL	97				
OIL APPLIANCES					
GRANT	100-105	FIREBIRD	106-109	FRANCO BELGE	110-111
GI I/ (IVI	100 100	I ITEBITO	100 103	THIN WOO BLEGE	110 111
HEATING CONTROLS					
COMMON CONTROLS MAP	114-115	COMMON CONTROLS	116	DRAYTON WISER	118-119
	120-121	WATER PUMPS	122		<u>_</u>
TOOLS & CONSUMAB	LES				
CLEANING EQUIPMENT	124-126	MISCELLANEOUS	127-129	SYSTEM CLEANERS	130-131
SAFETY ALARMS	132	BATTERIES	133	OIL TOOLS	134-135
HAND TOOLS					
ANALYSER KITS - ANTON	136-137	ANALYSER KITS - KANE	138	ANALYSER KITS - TPI	139





COMMERCIAL UNITS & SPARES INDEPENDENT SITE SURVEYS AVAILABLE UPON REQUEST



COMMERCIAL, BOILERHOUSE & COMBUSTION CONTROLS





BOILERS









Glow-worm



POTTERTON

WATER HEATERS

STREBEL



ANDREWS







RDB NEUTRAL OIL BURNERS

The Riello RDB series of one stage light oil and kerosene burners is available in eleven basic models, with an output ranging from 16.8 to 120 kW, in three different structures.

The models are available in light oil and kerosene versions, conventional flue and balanced flue, with or without the fuel pre-heater fitted. A new model has been specifically designed to meet the increasing trends towards high pressure working field demand.



No	Model
3513008	RDB1 Neutral Burner - 16.8 - 26.3kW
3513603	RDB2 Neutral Burner - 24 - 38.3kW
3748950	RDB3 Neutral Burner - 35.6 - 68.7kW

RDB BALANCED FLUE KIT

All the RDB series models are easily converted from conventional flue to balanced flue, by replacing the plastic screen on the air intake with the connector for the air supply pipe.

No: 3062774



R40 SINGLE STAGE OIL BURNERS

The Riello 40 G series of single stage light oil burners, is a complete range of products developed to respond to any request for home heating. The Riello 40 G series is available in eleven different models, with an output ranging from 12 to 240 kW, divided in four different structures.

All the models use the same components designed by Riello for the Riello 40 G series. The high quality level guarantees safe working.

No	Model	
20030780	R40 G3B 19kW - 35kW	
20030785	R40 G5 26kW - 60kW	
3746467	R40 G10 54kW - 120kW	
3747469	R40 G20 95kW - 213kW	
3748251	B40 G20S 95kW - 240kW	



ECOFLAM MAX OIL BURNERS ON/OFF TW

- New high efficiency fan ventilation system (HPV) allowing easy matching with boilers having high combustion chamber back pressure
- Sealed aluminium casing with a new modern design cover
- Compact burner dimension with low noise levels
- New air damper with progressive micrometric air regulation
- New electrical wiring simple to disassemble for easy maintenance
- Air damper with 60 or 80mm snorkel adaptor for conventional & balanced flue
- Combustion head easy to assemble and fully adjustable for fine set up
- Single bolt burner fixing and the possibility to firmly secure it to the flange in three different positions for easier maintenance
- Monoblock electrodes for easy and steady installation into the nozzle even after maintenance
- Hi-Low version available with compact hydraulic system (Max AB HS)
- Low NOx version with vellow flame developed by Ecoflam
- Max range available with "D" pump for light oil with viscosity up to 200 cTs
- Full memory & diagnostic capability

No	Model	Rate KW	Replaces
3142915	MAX 1 TC	17 - 41	Minor 1
3142710	MAX 1 TL	17 - 41	Minor 1
3142916	MAX 4 TC	20 - 59	Minor 4
3142715	MAX 4 TL	20 - 59	Minor 4
3142917	MAX 8 TC	47 - 105	Minor 8
3142717	MAX 8 TL	47 - 105	Minor 8
3142918	MAX 12TC	60 - 130	Minor 12
3142719	MAX 12 TL	60 - 130	Minor 12
3142729	MAX 15TC	73 - 190	Minor 15
3142730	MAX 15 TL	73 - 190	Minor 15
3142731	MAX 20TC	86 - 237	Minor 20
3142732	MAX 20 TL	86 -237	Minor 20
3142733	MAX 30TC	110 - 319	
3142734	MAX 30 TL	110 - 319	

DIAGNOSTIC TOOL

- Able to read burner memory Lock outs - What they are - How long the burner has run
- Easy to read symbols No flashing error code.
- Faults displayed such as No Air, No Fuel, Stray Light, Low Gas
- Reads Flame signal with Burner running Gas and Oil

No: **3142931**







ST SERIES OIL BURNERS

This burner is suitable for use with both light oil and kerosene with single stage on/off operation. Available for both conventional and ducted air options and is typically suitable for domestic and commercial hot water boilers.

Balanced flue available as an extra.

Key Features:

- Quick and easy installation
- Reliable and trouble free operation
- Industry standard components available



 Most components can be easily accessed allowing for easy maintenance

All Sterling burners have been designed in accordance with EN267.

No	Model
ST35 S1S 63	Sterling Light Oil Burner 14-28kW
ST40 S1S 63	Sterling Light Oil Burner 18-39kW
ST50 S1S 76	Sterling Light Oil Burner 24-66kW
ST90 S1S 80	Sterling Light Oil Burner 47-119kW
ST130 S1S 140	Sterling Light Oil Burner 59-158kW

M SERIES OIL BURNERS

This burner is typically suited for commercial hot water boiler and steam boiler systems.

Available for use with light oil Class D fuel with:

- Single stage on/off
- 2 stage high/low

Key Features:

- · Quick and easy installation
- Reliable and trouble free operation
- Industry standard components available
- Most components can be easily accessed allowing for easy maintenance

No	Model
MOL 200 S1L 187	71 - 202 kW Oil On/Off 1 Phase
MOL 200 T1L 174 2H	53 - 178 kW Oil High Low 1 Phase
MOL 350 S1L 172	107 - 350 kW Oil High Low 1 Phase
MOL 350 T1L 172 2H	95 - 350 kW Oil High Low 1 Phase





X SERIES OIL BURNER RANGE

The X Series oil burner range is the latest from EOGB, a company renowned for high quality, technical excellence and environmentally safe products.

Three models, with outputs ranging from 14-100kW, can be configured for conventional or ducted air inlets to suit installations in domestic, commercial and light industrial premises.

Suitable for use with Kerosene, Gas Oil and FAME based Bio Fuel blends up to B10 as standard. B30 spec can be supplied under special order.



No: **X400** 14-36 kW No: **X500** 34-62 kW No: **X600** 50-100 kW

BALTUR COMMERCIAL OIL BURNER RANGE

TECHNICAL AND FUNCTIONAL CHARACTERISTICS

- Single stage operation (on/off)
- High pressure mechanical atomisation of fuel using nozzle
- Ability to obtain optimal combustion values by regulating combustion air and blast-pipe
- Maintenance facilitated by the fact that the atomisation unit can be removed without having to remove the burner from the boiler
- · Manual air flow adjustment
- When using biodiesel light oil (fuel vegetable origin), the burner must be built with specific components: flexible hoses, line filter and pump.
- Equipped with one 7-pole connector, one flange and one insulating seal for boiler fastening, 2 flexible hoses, one line filter and one nozzle
- On request: longer blast tube, operation on biodiesel

Suitable for use with Gas oil, plus FAME based Bio Fuel blends up to B10 as standard. RME Bio fuels require Heavy Oil Burner specification. Burners suitable for higher blends are available.



No: BTL10 / 1 Stage No: BTL10 / 2 Stage No: BTL14 / 1 Stage No: BTL14 / 2 Stage No: BTL20 / 1 Stage No: BTL20 / 2 Stage No: BTL26 / 1 Stage No: BTL26 / 2 Stage




- Leading burner technology for over 90 years.
- Meeting the climate challenges of today and tomorrow.
- Maximising Efficiency and Minimising Emissions.
- The "No.1" choice for Specifiers.
- An extensive range to cover 10kW to 30,000kW.







Visit rielloburners.co.uk to find out more or phone on 01480 432144







BFP11-L3 PUMP

L/H Rotation 7-15 bar



BFP11-R3 PUMP

R/H Rotation 7-15 bar



No: 071N7141

BFP20-L3 PUMP

L/H Rotation 7-20 bar



No: 071N7155 **BFP20-R3 PUMP**

R/H Rotation 7-20 bar



No: 071N7168

BFP21-L3 PUMP

L/H Rotation 7-20 bar



No: 071N7169

BFP21-R3 PUMP

R/H Rotation 7-20 bar



No. 071N7156

BFP41-L3 PUMP

L/H Rotation 7-20 bar



No: 071N7157

BFP10-R3

R/H Rotation



No: 071N8213

BFP52E-L3 PUMP

Twin coil 24 litres/hour



No: 071N7253

BFP52E-L5 PUMP

L/H Rotation Twin coil 42 litres/hour



No: 071N3202

Solve your challenges with a diamond



10 times

longer lifetime in critical applications e.g. in heavy loaded conditions



Longer lifetime in heavy loaded conditions

Over the last few years oil burner applications have changed to be operated at higher pressures and with more insulation partly for noise reduction as well for energy savings resulting in harder working conditions for the pumps. This is why we have upgraded all service pumps to version 2.0 to meet the highest demands in the market.

Extra durable Diamond coil

The new extra durable Diamond Coils endure more than 5 times as many cycles in the crash test compared to previous service coils. The result has been proved in an extremely harsh crash setup demonstrating how Diamond Coils provide outstanding durability in heavy loaded conditions.







BFP DIAMOND COIL

Replaces standard coils. 220/240V



No: 071N1006

BFP DIAMOND TWIN COIL

For BFP52 pumps



No: 071N1007

BFP PUMP LEAD

300mm



No: 071G0205

BFP ARMATURE



No: 071N0050

BFP FLANGE



No: 071N0047

PUMP GAUGE CONNECTOR



Connector No: 3008876 'O' Ring No: 3007177

BFP RED CARTRIDGE FILTER



No: 071N0064

BFP DISC FILTER



No: 071N0063

BFP BYPASS SCREW

BFP 20 / 21 / 41 / 52E

2 Pipe = In

1 Pipe = Out

No: 071N0041

DANFOSS PUMP SERVICE TOOL



No: DANFTOOL



MECTRON PUMP

Suitable for G2, G3, G5, G10 R40 burners



RDB PUMP

Suitable for all Riello RDB burners



No: 020030953

No: 020031996

MECTRON PUMP COIL



No: **3002279**

RDB PUMP COIL



MECTRON PUMP ARMATURE



No: 3020437

RDB PUMP ARMATURE



No: 3007871

RIELLO PUMP SERVICE KIT



No: 3000439

RIELLO PUMP '0' RING



No: **3007175**

RIELLO BYPASS SCREW





RDB FILTER & SEAL



No: 20029299 No: 3020436





PUMP 32mm HUB

ACPE Rotation



No: AS47C1582

PUMP 54mm HUB

ACPE Rotation



No: AS47C7451

PUMP 32mm HUB

CPE Rotation



No: AS47A7564

SUNTEC COILS

240V

No: ASCOIL240V

110V

No: ASCOIL110V




HUB



No: ASHUB

FLANGE



No: ASFLANGE

LEAD

Suntec pump lead



No: **ASLEAD**

ARMATURE, COIL & LEAD



No: ASSOLENOID

DELTA PUMP COIL

DELTA VU PUMP 230V

Delta Universal



Delta



No: 1805999

No: 3700100





No: 3006911

RIELLO LONG AIR RAM



No: 3020444

RIELLO HYDRAULIC RAM SEAL



No: 3007132

BENTONE B9 AIR INTAKE ASSEMBLY



Intake No: **B03-00-117-58501** Gasket No: **B03-00-118-54401**

BENTONE B11 AIR DIAL



No: **B03-00-117-28001**

BENTONE B11 AIR FLAP



No: **B03-00-115-92901**

STERLING AIR ADJUSTMENT SCREW



MINOR 1 AIR INTAKE



No: **B03-00-120-70901** No: GRCA020

MINOR 4 AIR INTAKE



MINOR 1 SNORKEL



No: GRCA030

No: GRCA021

19





STERLING 30-50 THREE PIECE COUPLING

 $8mm \rightarrow 8mm \text{ shaft}$ Length 80mm



STANLEY THREE PIECE COUPLING

8mm → 13mm shaft



No: **B03-00-114-07210**

INTER 99 SMALL FLEXI DRIVE ROD

20mm Econo



No: **SY0100261527**

ELECTRO-OIL PUMP COUPLING

20mm Econo → 8mm shaft



No: C01-00-114-01009

RIELLO R40 DRIVE COUPLING

Shaft diameter 8mm



No: **C01-00-113-98202**

WHITE COUPLING

Shaft diameter 11mm



No: 3000443

ONE STEP COUPLING

Shaft diameter 8mm



No: **1209216**

ONE STEP COUPLING WITH LIP

Shaft diameter 8mm



No: 1209219

TWO STEP COUPLING

Shaft diameter 8mm



No: **C01-0005**

TWO STEP COUPLING WITH LIP

Shaft diameter 8mm



No: MP504 No: C01-0004



ECONO ROD

Length 1 Metre
1" Econo
Used with the pieces
below to create drive
couplings

No: **1701009**



ECONO DRIVE 8mm

1" Econo → 8mm shaft



ECONO DRIVE 11mm

1" Econo → 11mm shaft



No: 1701001

ECONO DRIVE 12.7mm

1" Econo → 12.7mm shaft



No: **1701003**

ECONO DRIVE FOUR SPLINE

1" Econo → 4 Spline



No: **1701005**

SIMEL MOTOR FLANGE

PCD 130mm Shoulder 110mm



No: **1701008**

SIMEL MOTOR FLANGE

PCD 172mm Shoulder 140mm



No: 1209222

MOTOR BEARINGS



No: **1209221**

MOTOR LEAD

Three Pin



Simel No: **BS6201ZE**Riello No: **BS03040**No: **E1109/2**







B11 BURNER MOTOR

Hanning Shaft 8mm 90W

No: BN12090101

STERLING 90/146 BURNER MOTOR

Hanning Shaft 8mm 125W



2011, 2010, 2020 BURNER MOTOR

AACO Shaft 8mm 90W



No: BN12090001

STERLING 35, 40, 50 BURNER MOTOR

AACO Shaft 8mm 90W



EOGB X400 BURNER MOTOR

AACO Shaft 8mm 90W



INTER 10 11 12 989 & 109 BURNER MOTOR

AACO Shaft 8mm 90W



INTER 10/109/99+D42 BURNER MOTOR

Simel Shaft 8mm 90W



RIELLO RDB MOTOR

Riello Shaft 13mm 90W





RIELLO MECTRON BURNER MOTOR

Riello Shaft 13mm 90W

No: A02-037R

No: 3007971



Motor accessories included are correct at time of printing, but subject to change at any time. E & O.E



RIELLO G20/G20S BURNER MOTOR

Riello Shaft 13mm 150W



No: 3005820

RIELLO RDB4 BURNER MOTOR

Riello Shaft 13mm 130W



No: 3008964

MINOR 1-4 BURNER MOTOR

Simel Shaft 13mm 70W



No: 1109024

MINOR 1-4 BURNER MOTOR

Simel Shaft 13mm 75W



No: 1109006

MINOR 8 BURNER MOTOR

Simel Shaft 13mm 100W



No: 1109007

MINOR 12 BURNER MOTOR

Simel Shaft 13mm 130W



No: 1109008

MINOR 1-4 STANLEY BURNER MOTOR

Simel Shaft 13mm 70W



No: 1109020

ECOFLAM MAX 1 BURNER MOTOR

Simel Shaft 13mm 75W



No: M181/12

ECOFLAM MAX 4 BURNER MOTOR

Simel Shaft 13mm 90W



No: M181/21

ECOFLAM MAX 12 BURNER MOTOR

Simel Shaft 13mm 130W



No: M181/32

Motor accessories included are correct at time of printing, but subject to change at any time. E & O.E.



STERLING B9 CAPACITOR

Thin Spade 3uf



STERLING B11 CAPACITOR

Thin Spade 4uf



No: **B03-00-120-93301**

SIMEL CAPACITOR

3.5uf



No: **B03-00-115-96501**

SIMEL CAPACITOR

4uf



No: **1290000**

RIELLO RDB CAPACITOR

4uf



No: **1290001**

RIELLO RDB CAPACITOR

4.5uf



No: 20087035

RIELLO RDB CAPACITOR

5uf



No: 20071576

RIELLO MECTRON CAPACITOR

4uf



No: 20081251

RIELLO G20, RLS/28/38/50 CAPACITOR

5uf



No: 20087025

ECOFLAM CAPACITOR

2uf

50W motors



No: **20087027** No: **C107**

ABGO

ECOFLAM 480K MXE CAPACITOR

6.3uf Suitable for Rayburn M181/32



ECOFLAM MAX 1-4 CAPACITOR

3uf Max 1-4



No: C107/12

ECOFLAM MINOR 12 CAPACITOR

6.3uf 130W motors Minor 12



No: **C107/9**

ECOFLAM MAX 8 CAPACITOR

4uf Max 8



No: C107/3

ECOFLAM MINOR 12 CAPACITOR

5uf Minor 12



No: C107/10

ECOFLAM MAX 12 CAPACITOR

5uf Max 12



No: C106/3

INTER CAPACITOR

5uf Fits A02-037R motor



No: **65325038**

UNIVERSAL CAPACITOR

3uf



No: BN11596502

UNIVERSAL CAPACITOR

4uf



No: **RM3MFD**

UNIVERSAL CAPACITOR

5uf



No: RM4MFD

No: **RM5MFD**







B₉B

Diameter 97mm Thickness 33mm Shaft 8mm



No: **B03-00-117-56601**

B11 2011

Diameter 108mm Thickness 41mm Shaft 8mm



No: **B03-00-115-92701**

STERLING ST35

Diameter 97mm Thickness 41mm Shaft 8mm



No: **B03-00-114-17603**

STERLING ST40

Diameter 108mm Thickness 41mm Shaft 8mm



No: **B03-00-114-17604**

STERLING ST50

Diameter 120mm Thickness 42mm Shaft 8mm



TEHEMA 0100

Diameter 146mm Thickness 51mm Shaft 8mm

ST146



No: **B03-00-114-17601**

No: BN11872601

PUNKER BOXER FAN PUNKER

Diameter 108mm Thickness 62mm Shaft 8mm



Diameter 133mm Thickness 62mm Shaft 8mm



No: **D04-006S**

No: **D05-010S**

NU-WAY WRAC-632800161

Diameter 158mm Thickness 73mm Shaft 13mm



No: **D06-001X**

B20

Diameter 133mm Thickness 51mm Shaft 8mm



No: **B03-00-117-27601**

Ecoflam



MINOR 1

Diameter 99mm Thickness 43mm Shaft 13mm



No: BFV10001/001

MINOR 1

Diameter 99mm Thickness 34mm Shaft 13mm



No: BFV10003/001

MINOR 4

Diameter 120mm Thickness 60mm Shaft 13mm



No: **BFV10053/001**

MINOR 8 12

Diameter 124mm Thickness 59mm Shaft 13mm



No: BFV10055/001

MAX GAS

Diameter 120mm Thickness 50mm Shaft 13mm



No: BFV10060/001

INTER 10 99

Diameter 108mm Thickness 42mm Shaft 8mm



No: **B03-0015**

RIELLO R40 G2 G3 G5 FAN WHEEL

Diameter 108mm Thickness 41mm Shaft 13mm



No: 3005708

RIELLO G10 FAN WHEEL

Diameter 120mm Thickness 51mm Shaft 13mm



No: 3005788

RIELLO G20 FAN WHEEL

Diameter 140mm Thickness 62mm Shaft 13mm



No: 3005799





B9, 2011, STERLING 30, 40 & 50 B20B



STERLING BLOCK KIT 35,40 & 50



No: **B03-00-115-93701**

No: **B03-00-118-86701**

STERLING 90 & 130



INTER B30 20/40



No: **B03-00-119-24301**

No: **B03-00-119-24401**

EOGB 200MM



EOGB 275MM



No: **E01-0001**

D11-A36 & D11-F55





No: G05-0045

No: G05-0068

No: **B03-94-390-81815**

D13, D16, D18 & D22



RAYBURN 400 SERIES NUWAY

INTER 10, 12 99 & 109 PAIR



No: **R2625**

Ecoflam



MINOR 1-8 BLOCK

Ecoflam



No: **BFE01102**

MINOR 1-8 KIT

Ecoflam Kit to replace x2 singles



No: GREL007

MINOR 12, 20 & 30 BLOCK

Ecoflam



No: **BFE01103**

MINOR 12, 20 & 30 SINGLES

Ecoflam



No: GREL002

RIELLO G3 R40 BLOCK



No: 3005721

RIELLO G5 R40



No: **3005711**

RIELLO RDB 1 & 3



No: 3007513

RIELLO RDB 2



No: 3008860

GP ANGLED ELECTRODE

RIELLO RDB 3.2





No: **R1458**



EBI ACCESSORY KIT

2x secondary cables with Ø4 plugs 2x Ø44mm plugs 2x Ø6.35 mm plugs



No: 052F0061

STERLING 35 40 50 90 130 IGNITION LEADS

Length 300mm For standard length tubes.



No: **B03-00-120-67930**

EOGB X SERIES IGNITION CABLE

Length 370mm



No: E80-0601

MINOR 1 HT LEAD

Length 235mm



No: BFE01401/1

MINOR 8-12 HT LEAD

Length 425mm

No: BFE01401/4

INTER B20 IGNITION LEADS

Length 300mm



No: **B03-00-120-67830**

B11 IGNITION LEAD

Length 400mm



No: **B03-00-120-68020**

INTER TRANSFORMER LEAD

Length 750mm



No: F04PATB7505

MINOR 4-8-12 HT LEAD

Length 325mm



No: BFE01401/2

UNIVERSAL HT LEAD

Length 350mm 2.8mm Flat spade connections



350mm No: **3153001** 1000mm No: No: **3153005**

ABGO

RIELLO HT LEAD

Length 600mm



RIELLO HT LEAD

Length 170mm



No: 3012393

NO. **3000**

No: **3008794**

UNSHROUDED RAJAH CONNECTION



SEMI SHROUDED RAJAH CONNECTION



No: 3600100

No: **3600103**

FULLY SHROUDED RAJAH CONNECTION



IGNITION LEAD MULTI-KIT

1500mm lead & accessories



No: 3600105

No: REG-C30

XGN GREEN 4 PIN BURNER PLUG



WEILAND 7 PIN BURNER PLUG

Male No: **B08-052J** Female No: **B08-046L** Male No: **B08-049X** Female No: **B08-047M**

MULTIFUNCTION LOOP TESTER WITH TEST LEAD KIT

Multi-Function electrical checker designed specifically for checking heating appliances.

4 in 1 RCD tester - loop, mains voltage, correct wiring and correct polarity.

Carry case and manual included.

No: REG-XP5









No: 052F4064

INTERMITTENT PATTERN

Danfoss



No: 052L0030

DOUBLE OUTLET INTERMITTENT

Danfoss 240V Oil



No: 052L0003

E820 DOUBLE OUTLET OIL



No: **T125-1**

No: 3401020

INTERMITTENT DOUBLE OUTLET

10kV



FIDA EBI4

Twin Outlet c/w Lead



INTERMITTENT 240V

Danfoss With feet Inter 99

No: 052L0082

SATRONIC 0.25A

50/60Hz 33% In 3 Min



No: **ZT930-240V**

INTERMITTENT DOUBLE OUTLET

Oil 2x 4kV 33%



No: **3400820**

ZT812-1



No: **ZT812-1**

ENGINEERING TOMORROW



Oil burner maintainance

Maintainance means reliability

Your oil burner needs the same attention as your car in order to perform at its best. It takes regular cleaning, inspection and servicing to make sure it's in perfect shape and running in a reliable way.

A well-adjusted oil burner is far more efficient and can save you up to 10% or even more in oil use. If soot builds up, the oil use will go up with 2-4% per mm soot layer.



To obtain savings and minimize risk the annual service should include:



Replacement of

Save up to
10%
in oil use
with an annual
burner service

An annual service will help ensure:

Replacement of



Cleaning an fine tuning





Energy savings



Money



Minimum pollutions



Longer burner lifetime



Avoid



Greener heating

Danfoss A/S · Heating Segment · Haarupvaenget 11 · 8600 Silkeborg · Denmark Tel.: +45 7488 8000 · Email: heating@danfoss.com · www.heating.danfoss.com

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All tademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss / Danfoss





SIEMENS

TF830.3 CONTROL BOX

Single Stage 240V

Photocell = M7(Sold Seperately)

No: **TF830.3**



TF974 CONTROL BOX

Single Stage 240V

Photocell = M7 (Sold Seperately)

No: **TF974**



TM0720-4 MOD35 CONTROL BOX

Single or Two Stage 240V

TF832.3 CONTROL BOX

Two Stage

Photocell = M7

No: **TF832.3**

(Sold Seperately)

240V

Photocell = M7(Sold Seperately)

No: TM0720-4



DKO 970 MOD5

Single Stage 240V

Photocell = M7(Sold Seperately)

No: **DKO-970 MOD5**



DKO 970 MOD21

Single Stage 240V

Photocell = M7(Sold Seperately)

No: DK0-970 MOD21



DKO 972 MOD5

Two Stage 240V

Photocell = M7(Sold Seperately)

No: DK0-972

LOA24.171.B2B

Single Stage 240V

Photocell = QRB (Sold Seperately)

No: LOA24.171.B2B



DKO 972 MOD5 (110V)

Two Stage 110V

Photocell = M7(Sold Seperately)

No: DK0-972 MOD5



OBC82.10

Single or Two Stage 240V

Photocell = LD or LDS (Sold Seperately)

No: 057H8102







RIELLO MECTRON CONTROL BOX

530SE

Photocell = 3002280 (Sold Seperately)

No: 3001156

RIELLO MECTRON BASE

Base for 530SE



No: 3002278

RIELLO RDB CONTROL BOX

535RSE/LD

Photocell = 20132526 (Sold Seperately)

Standard box No: 3008652

RIELLO RDB DIGITAL CONTROL BOXES



LOA BASE

Base for Siemens LOA control boxes.



LOA BASE PLATE

Siemens



No: 057H7010 No: 2031101

UNIVERSAL BASE

Satronic TFI, MMG, MMI



Base No: S-98

Entry Plate No: S-98PLAT

TMO BASE

Satronic



No: TMOBASE

ADAPTER BASE FOR BH011 - TF830



Satronic

No: **US930**

BHO TO OBC ADAPTER BASE KIT

Danfoss



No: 057H7224







MZ PHOTOCELL SHORT

Satronic



MZ PHOTOCELL LONG

Satronic 80mm



No: MZ770S

MZ/FZ PHOTOCELL LEAD

Satronic 750mm



No: MZ770-80

MZ PHOTOCELL FLANGE

Satronic



No: **LEAD**

MZ/FZ STRAIGHT LEAD

Satronic



No: MZFLANGE

LD STANDARD PHOTOCELL

Danfoss



No: S01-FZ711S-030

LD LONG PHOTOCELL

Danfoss



Old No: 057H7081 New No: 057H7107

LDS PHOTOCELL

Danfoss

Extra Sensitive



Old No: 057H7087 New No: 057H7109

LDS CLIP

Danfoss



LDS FLANGE

Danfoss



No: 057H7072

No: 057H7071



SIEMENS

ABGO



Landis & Gyr



QRB1 RED PHOTOCELL

Landis & Gyr Extra Sensitive



No: QRB1

RIELLO RDB PHOTOCELL

Large



No: **QRB1B**

RIELLO RDB PHOTOCELL

Small



Digital No: **20132550** Analogue No: **20132526**



No: 20132553

RIELLO MECTRON PHOTOCELL

Riello



SIEMENS IRD1010.1 PHOTOCELL



Old No: **3002280** No: **20132573**

REMOTE RESET

For Satronic control boxes. 200mm



No: IRD1010.1

QRA2 PHOTOCELL

Landis & Gyr



No: FR870

UVZ780 RED

Satronic



No: QRA2

UVZ780 BLUE

Satronic



No: **UVZ780R**

No: UVZ780B



RIELLO RDB T3 BLAST TUBE

Length 100mm



No: 3002447

RIELLO RDB T1 BLAST TUBE

Length 100mm



No: 3002507

RIELLO RDB T5 BLAST TUBE

Length 100mm



No: 3002533

RIELLO G5 BLAST TUBE

Length 80mm



No: **3005706**

RIELLO R40 CUP SHAPED BLAST TUBE

Length 100mm



No: 3005775

RIELLO R40 CUP SHAPED BLAST TUBE

Length 110mm



No: **3006001**

RIELLO RDB4 G10 BLAST TUBE

Length 113mm



No: 3006151

RIELLO RDB CUP SHAPED BLAST TUBE

Length 110mm



No: 3008768

RIELLO RDB CUP SHAPED BLAST TUBE

Length 110mm



No: 3008769

RIELLO RDB CUP SHAPED BLAST TUBE

Length 67mm



No: 3008859

2011 BLAST TUBE

Length 77mm



No: **B03-960-13000**

2011 BLAST TUBE

Length 125mm Spec: PL6-7-24-10



No: **B03-960-00001**

ELECTROIL BLAST TUBE

Length 77mm



No: **B03-960-00100**

B9 BLAST TUBE

Length 77mm



No: **B03-960-00200**

ST146 KA BLAST TUBE

Length 94mm



No: **B03-00-117-28401**

EOGB X400 BLAST TUBE

Length 82mm



No: **E80-0102**

B20 BLAST TUBE

Length 147mm



No: BN11728402

ECOFLAM REDFYRE 60/80 BLAST TUBE

Length 72mm



No: **BFB01021/002** Alt. No: **65320267**

ECOFLAM ALPHA BLAST TUBE

Upfiring Length 92mm







ECOFLAM RAYBURN PJ BLAST TUBE

ECOFLAM STANLEY 60K BLAST TUBE

Length 72mm



No: BFB01002/002

Alt. No: 65320255

ECOFLAM MINOR 1 BLAST TUBE

Upfiring Length 95mm

No: BFB01016/002 Alt. No: 65320265



Length 72mm



No: BFB01104/002

Alt. No: 65320284

ECOFLAM DONARD 60K 90K BLAST TUBE

Length 174mm



No: BFB01003/002 Alt. No: 65320256

ECOFLAM STANLEY 80 BLAST TUBE

Length 72mm



No: BFB01014/002

Alt. No: 65320263

ECOFLAM BRANDON BLAST TUBE

Upfiring Length 95mm

No: BFB01029/002 Alt. No: 65320270



ECOFLAM DONARD 80K BLAST TUBE

Length 115mm



No: BFB01052/202

Alt. No: 65320275

ECOFLAM 80K BOILER BLAST TUBE

Length 72mm



No: BFB01153/002

Alt. No: 65320286

ECOFLAM BLAST TUBE

ECOFLAM BRANDON TWIN BLAST TUBE

Length 113mm



Length 72mm

No: BFB01071/001





ABGC

MINOR 1 NOZZLE HOLDER



No: GRCR009/10

STANLEY MINOR 1 NOZZLE HOLDER



No: GRCR009/15

ECOFLAM ST/ST ELBOW

1/8"



Male \rightarrow Male No: **Y1000/1** Male \rightarrow Female No: **Y418**

B9 NOZZLE HOLDER

Length 165mm



No: **B03-00-117-56901**

RIELLO MECTRON NOZZLE HOLDERS



G2 G3 G5 80mm No: **3005724** G5 G7 91mm No: **3005709**

MINOR 4 NOZZLE HOLDER



No: **GRCR010/100**

MINOR NOZZLE HOLDER NUT & OLIVE



BENTONE B9 B11 CHECK VALVE

No: **B03-00-119-13201**

B9 NOZZLE HOLDER

Length 212mm



No: **B03-00-117-56902**

RIELLO RDB NOZZLE HOLDERS



RBD1 RDB2 90mm No: **3008642** RBD4 125mm No: **3008654**



WORCESTER PRESSURE JET GASKET

Foam Thickness 8mm



X400 '0' RING

Diameter 90mm Thickness 5mm



No: 87161409020

STERLING 35 40 50 90 GASKET

Foam Width 150mm Height 150mm Thickness 4mm



No: **E80-0202**

INTER 10 11 12 99 & B9 B11 GASKET

Foam Width 164mm Height 114mm Thickness 4mm



No: **B03-00-118-54201**

RAYBURN 400 SERIES GASKET

Foam Suitable for all 400 series twinhead burners.



No: **B03-04-390-12027**

RAYBURN BURNERTECH GASKET

Foam Suitable for 400 series cooker only burners. (Burnertech) Gas



No: **R3798**

RIELLO RDB1 RDB2 GASKET

Fibre Width 172mm Height 135mm Thickness 4mm



No: **R4896**

RIELLO R40 G10 GASKET

Fibre
Width 183mm
Height 160mm
Thickness 4mm



No: 3005787

RIELLO NEOPRENE 'O' RING

Diameter 87mm



No: **3005795**

EOGB 1 BOLT GASKET

Foam Width 11mm Inside Diameter 86mm Thickness 3mm



No: **3007178**

No: **B03-00-118-83101**

ECOFLAM MINOR 1 GASKET

Fibre Width 182mm Height 137mm Thickness 4mm



ECOFLAM MINOR 4 GASKET

Fibre Width 177mm Height 144mm Thickness 4mm



No: **BFG02016**

ECOFLAM MINOR 1 GASKET

Neoprene Width 151mm Height 123mm Thickness 5mm



No: BFG02009/1

ECOFLAM MINOR 4 GASKET

Neoprene Width 177mm Height 144mm Thickness 5mm



No: BFG02008/3

THERMECON MINOR 1 GASKET

Neoprene Width 151mm Height 116mm Thickness 9mm



No: BFG02009/3

THERMECON MINOR 4 GASKET

Neoprene Width 182mm Height 150mm Thickness 10mm



No: TH01111382

ALPHA CLEAR GASKET

Clear Width 140mm Height 116mm Thickness 4mm



No: **TH01111383**

ALPHA RED GASKET

Neoprene Width 11mm Inside diameter 87mm Thickness 3mm



No: **BFG02028**

STANLEY MINOR 1 GASKET

Neoprene Width 165mm Height 126mm Thickness 5mm



No: **BFG02019**

CERAMIC GASKET MATERIAL

Thickness - 2mm 1000mm x 600mm



No: TH01111382

No: **CERPAPER2**





DANFOSS OIL NOZZLES

Developed for optimum combustion of kerosene in domestic oil burners. Oil nozzles type EH and ES are designed for domestic high-pressure oil burners operating with kerosene.

The nozzles are equipped with sintered bronze filters.

Existing oil nozzles e.g. S and H can directly be replaced by the new ES - EH.

Identification

The nozzle is marked with the following information:



OFTEC-specification

1.80 Specified capacity (kg/h)

OFTEC speci- 800 kPa (8 bar), 1.65 cSt., fication point 790 kg/m³

ion point 790 kg/m³ Capacity tolerance: ± 5%

OK OFTEC Kerosene certification

Serial number for internal use

0.60 Reference capacity (USgal/h)

Reference 700 kPa (7 bar), 3.4 cSt., specification 820 kg/m³

point:

60° ES Spray angle & pattern (EH = Hollow) (ES = Solid) Oil nozzles type EH and ES are designed for domestic high-pressure oil burners operating with kerosene. They are available with 2 different spray angles and sizes from 0.4 to 1.10 USgal/h.

The nozzles are equipped with sintered bronze filters.

Our existing oil nozzles e.g. 60°S and 80°H can directly be replaced by our new 60°ES - 80°EH,


Application and Features

- Kerosene
- . OFTEC certification (OFS E100)
- . 100% test of capacity and performance

Design


Sizes 0.40-0.60 USgal/h with O-ring sealing


- A Nozzle housing
- C Nozzle cone D Orifice disc
- H Filter
- S O-ring holder





Sizes 0.65-1.10 USgal/h with bottom screw













CONVERSION CHART

		1sт	2 _{ND}
		CHOICE	CHOICE
DELAVAN A	\rightarrow	Н	HFD/HD
DELAVAN B	\rightarrow	S	SFD/SD
FLUIDICS SF	\rightarrow	SFD	S
FLUIDICS HF	\rightarrow	HFD	Н
FLUIDICS S	\rightarrow	SD	S
FLUIDICS H	\rightarrow	HD	Н
MONARCH PL	\rightarrow	H/B	
MONARCH NS	\rightarrow	HFD	Н

		1st CHOICE	2 _{ND} CHOICE
MONARCH PLP	\rightarrow	В	
Monarch AR	\rightarrow	SFD	S
MONARCH R	\rightarrow	SFD	S
STEINEN PH	\rightarrow	H/B	
STEINEN H HT	\rightarrow	HFD	Н
STEINEN SS	\rightarrow	В	
STEINEN S ST	\rightarrow	SFD	S
STEINEN Q	\rightarrow	SFD	B/S

RAYBURN

360K Ecoflam	R2989	0.65-80SF
480K MKI Cooker Side	R2510	0.40-80SF
480K MKI Boiler Side	R2511	0.65-80SF
460 Boiler Side	R3770	0.55-80EH
480 Boiler Side	R3771	0.65-80EH
499 Boiler Side	R3772	0.85-80EH
460, 480 & 499 Cooker Side	R3773	0.40-80EH
400K MKI Cooker Only	R2510	0.40-80SF
400K MX Cooker Only	R3773	0.40-80EH
400K Power Flue Cooker Only	R3773	0.40-80EH
460K, 480K, 499K MKII Cooker Side	R2510	0.40-80SF
460K MKII Boiler Side	R3122	0.55-80ES
480K MKII Boiler Side	R2511	0.65-80S
499K MKII Boiler Side	R3599	0.60-60\$

WORCESTER BOSCH

Technical Information regarding Worcester GREENSTAR Boilers. The following selection chart shows the oil nozzle fitted to the relevant GREENSTAR Boilers.

Boiler	Output	Nozzle
Camray 25/32	25	0.65 80EH
	27.5	0.75 80EH
	30	0.85 80EH
Camray 18/25	18	0.55-80EH
	21.5	0.60-80ES
	25	0.75-80ES
Camray 12/18	12	0.40-60ES
	15	0.45-60ES
	18	0.55-80ES
Utility 32/50	32	0.85-60ES
	41	1.10-45S
	50	1.25-45S
Danesmoor 18/25	18	0.50-80EH
	21.5	0.55-80EH
	25	0.65-80EH
Utility 50/70	50	1.25-45S
	60	1.50-45S
	70	2.00-45S
Heatslave 25/32	25	0.75-60ES
	28.5	0.75-60ES
	32	0.85-60ES
Heatslave 12/18	12	0.35-80SR
	15	0.40-80ES
	18	0.50-80ES

DANFOSS NOZZLE BOX

Holds 40 nozzles



No: NOZBOX





DELAVAN NOZZLES FOR OIL BURNERS RUNNING KEROSENE FUEL

Delavan created its nozzle using bi-metal construction. The brass body and stainless steel metering parts permit machining to close tolerances for precision and consistently high performance.

BRASS transmits heat fast from the nozzle face to reduce the possibility of varnish and oil residue build-up.

STAINLESS STEEL provides that extra Durability for metering parts where wear is a factor.

TYPE W nozzles are neither truly hollow nor solid. These nozzles frequently can be used in place of either solid or hollow cone nozzles between 0.40 and 8.00GPH, regardless of the burner's air pattern.

Precise spray angles and optional spray uniformity through new machining process



Reduced distributor size with shorter tangential slots to avoid plugging

Aerodynamic body configuration Rolled threads to avoid metal chips and burrs

Sintered filter for maximum protection; sized depending on flow. Mesh strainer supplied on 2.00 GPH and higher flow rates.

100% Tested

Every nozzle tested.
Then we go one step further and clean the test oil from the nozzle to avoid plugging.

NOZZLE REMOVING TOOL



No: G26-001W

ABGO NOZZLE BOX

Holds 100 nozzles









OIL LINES

F0L445

BRAIDED	
F0L210	500mm - 1/4" Female X 1/4" Female
F0L220	600mm - 1/4" Female X 1/4" Female
F0L230	750mm - 1/4" Female X 1/4" Female
F0L250	1000mm - 1/4" Female X 1/4" Female
F0L310	500mm - 1/4" Male X 1/4" Female
F0L320	600mm - 1/4" Male X 1/4" Female
F0L330	750mm - 1/4" Male X 1/4" Female
F0L350	1000mm - 1/4" Male X 1/4" Female
F0L441	900mm - 1/4" Female Elbow X 1/4" Female
F0L442	900mm - 1/4" Male Elbow X 3/8" Female
F0L443	900mm - 1/4" Female Elbow X 3/8" Female
F0L444	700mm - 1/4" Male Elbow X 1/4" Female

700mm - 1/4" Female Elbow X 1/4" Male



*Best Sellers

LONG LIFE RUBBER (GREEN BIO)

FUL51U	500mm - 1/4" Female X 1/4" Female
F0L530	700mm - 1/4" Female X 1/4" Female
F0L550	1000mm - 1/4" Female X 1/4" Female
FOL640	200mm - 1/4" Male Elbow X 1/4" Female
FOL641	900mm - 1/4" Female Elbow X 1/4" Female
F0L642	900mm - 1/4" Male Elbow X 3/8" Female
FOL643	900mm - 1/4" Male Elbow X 1/4" Female
F0L741	900mm - 1/4" Male Elbow X 1/4" Female Elb

F0L741 900mm - 1/4" Male Elbow X 1/4" Female Elbow **F0L742** 900mm - 1/4" Female Elbow X 1/4" Female Elbow

RUBY RED (BRAIDED WITH POLYURETHANE COVER)

F0L941	900mm - 1/4" Female Elbow X 1/4" Female
F0L942	900mm - 1/4" Male Elbow X 3/8" Female
F0L943	900mm - 1/4" Male Elbow X 1/4" Female

CLEAR

F0L800 700mm - 1/4" Female Elbow X 1/4" Female

OIL LINE NIPPLE

1/4" Coned x 1/4" BSP



OIL LINE NIPPLE

1/4" Coned x 1/4" BSP Tapered



No: 2405005LL

OIL LINE NIPPLE

3/8" Coned x 1/4" BSP



No: **2407060**

OIL LINE NIPPLE

3/8" Coned x 3/8" BSP



No: 2407061

OIL LINE NIPPLE

3/8 Coned x 1/4" BSP Tapered



No: 2407062

COPPER WASHER

For 1/4" Thread



No: 2407069

NON RETURN OIL VALVES

1000

No: CW04

COMPRESSION BALL VALVE

10mm Compression connections



1/4" No: **2004000** 3/8" No: **2004001**

LEVER BALL VALVE



M/F BALL VALVE

No: 400 10 300

Female → Male



1/4" No: **VACP9014** 3/8" No: **VACP9038**

1/4" No: **VACP40514** 3/8" No: **VACP405010**



SHALLOW BOWL COMPLETE



No: 1/4"- **CR18489** No: 3/8"- **CR19489**

DEEP BOWL COMPLETE



No: 1/4"- **CR18493** No: 3/8"- **CR19493**

SHALLOW BOWL ELEMENT

Crosland 489



DEEP BOWL ELEMENT

Crosland 493



No: **CR489**

BIO SHALLOW BOWL COMPLETE



No: 1/4"- **CR18489B** No: 3/8"- **CR19489B** No: **CR493**

BIO DEEP BOWL COMPLETE



No: 1/4"- **CR18493B** No: 3/8"- **CR19493B**

BIO SHALLOW BOWL ELEMENT

Bio 489



BIO DEEP BOWL ELEMENT

Bio 493



No: CR489-B

FILTER ELEMENT 414



No: CR493-B

FILTER ELEMENT 555



No: **CR555**

FILTER ELEMENT 4009



No: CR4009

GOK FILTER HOUSING

3/8" connections



No: **1300000**

WASHABLE FILTER ELEMENT



No: **E03-034Q**

MANN W712 FILTER

For use with Gok 1300000



No: MANW712

FILTER BOWL COMPLETE 3/8"



No: 38FILTER

MESH FILTER ELEMENT 3/8"

For use with 38FILTER



No: 38ELEMENT

OIL FILTER ISOLATION VALVE



No: **OFV1**

OFV1 FILTER ELEMENT



No: AVF1000K

ALUMINIUM FILTER BOWL 1/2"

Includes washable filter.



No: A02-70302/AL

GEM 4000 FILTER ELEMENT



No: CTGEM4000



TANKMASTER FILTER ELEMENT



No: TM4660F

NYLON FILTER ELEMENTS 42mm



No: TM4660F-10

CENTRO 1/4" ALUMINIUM FILTER



No: **GA-V7045201ALS**

CENTRO FILTER ELEMENT



No: GA-U604500015

CENTRO FILTER BRACKET



No: **GA-V70410**

UNIVERSAL TANK FILTER

'One kit fits all'



No: ABTANKFILTER

NYLON FILTER '0' RINGS

Pack of 10



No: **TM4660F-0**

CENTRO 3/8" ALUMINIUM FILTER



No: GA-V7045101ALS

CENTRO 'O' RING SEAL KIT



No: GA-U03198

FILTER ELEMENT FOR GOK GS2000




No: **3006025**



Engineer Accessories

Talk to us today about the full range of Anglo Nordic Engineered Products!



Anglo Nordic Fire Valve Tester

Designed and engineered by Anglo Nordic to be safe, cost effective, and faster than other testers.

- 0°C 120°C Thermostat
- 3-Minute Testing Time
- 230V Operation
- Ultra-Rugged Design
- Fits All Types of Capillary Fire Valves











UCV with single outlet.



TANK KIT B

UCV with single 90° outlet.



No: TANKKITA

TANK KIT C

UCV with double 90° outlet.



TANK KIT D

No: TANKKITB

UCV with double outlet.



No: TANKKITC

NEW STYLE ULTRA COMPACT VALVE



Short Handle No: UCV-S Long Handle No: UCV-L

ISOLATION FILTER



No: UCV-FILTER

ΔBGO



ULTRA COMPACT VALVE

Requires key to operate.



No: UCV

COMPACT VALVE KEYS



ELBOW 90°



TEE



No: UCV-ELB

OFFSET TEE

For adding a third or fourth filter and line. (Or more)




No: UCV-TEE

RETRO FIT HANDLE

Kit to install new style handle to older UCVs. (Includes new filter assembly)

No: UCV-RET





No: UCV-EXT-75MM

No: UCV-EXT-100MM No: UCV-EXT-150MM No: UCV-EXT-125MM No: UCV-EXT-200MM



REPLACEMENT HANDLES

Includes a thin walled socket to remove and replace handle.

10x Short Handles No: UCV-SH-10 10x Long Handles No: UCV-LH-10

5x Long, 5x Short Handles No: UCV-MH-10





TOBY KNOB TYPE OCV'S




4-8cc No: **3904200** 4-13cc No: **3904205**

TOBY TRADITIONAL OCV'S

3-9.5cc No: 4-13cc No: 4-20cc No: 6-19cc No:



TOBY ELECTRIC TOP





TOBY ADAPTOR PLATE

To enable use with BM style float valves.



No: **3904029**

TOBY HOT ROD



TOBY GASKET

Suitable for all DVR 5 float controls



No: **3904057** No: **3904059**

OIL SOLENOID VALVES

Viton seals for use with kerosene.
Working pressure 0-16bar.
Available in 12V, 24V, 110V or 230V.
Normally Closed - Energise to open.
Opening/Closing time 30ms.
Solenoid valve can be mounted in any position without affecting performance.
(Coil must be used in vertical position).



1/8" N/C Solenoid - Viton Seal	\$1010.00.040-1/8V\$
1/4" N/C Solenoid - Viton Seal	\$1010.01.050-1/4V\$
3/8" N/C Solenoid - Viton Seal	\$1010.02-3/8V\$
1/2" N/C Solenoid - Viton Seal	\$1010.03-1/2V\$
3/4" N/C Solenoid - Viton Seal	\$1010.05-3/4V\$
1" N/C Solenoid - Viton Seal	\$1010.05-1V\$
1 1/4" N/C Solenoid - Viton Seal	\$1010.06-11/4V\$

(A)

TIGERLOOP DE-AERATOR

Original, outdoor fitment. A Tigerloop makes a one-pipe system possible for all types of oil heating installations helping to ensure environmental safety, cost effectiveness and reliability. In an oil heating system using a Tigerloop, all oil passes through the automatic oil de-aerator, which effectively removes all gas/air bubbles from the system. This eliminates oil pump and nozzle problems associated with gas/air in the oil.

Tigorio

No: **B03-00-117-48901**

INDOOR METAL TIGERLOOP BIO DE-AERATOR

The Tigerloop Bio model is constructed externally of metal materials making it suitable for both indoor and outdoor installation in the UK & IE. With the addition of a simple to fit 10mm vent pipe the removed air can be vented safely to the outside, ensuring only pure oil is passed through to the burner.



No: 3008024

FLOCO DE-AERATOR

Flow-Control 3/K-1 is for fuel oil (DIN 51603-1), diesel (DIN EN 590) also biodiesel and vegetable oils (rape oil). The device must not be subjected to undiluted additives, alcohol and acids. TÜV-tested (S 159/02)





GOK DE-AERATOR

c/w Filter. GS 2000 is a combination of an oil filter, de-aerator and shut-off valve. It is designed to be installed on oil combustion plants running on a single pipe system. With this system, a return pipe to the tank becomes superfluous which lowers costs and reduces the risk of damage to the environment in the event of a leak.





GOK ANTI-SIPHON VALVE 3/8"

Prevents oil siphoning on installations requiring suction lift. Also works as a safety device should an oil leak occur.

Adjustable version can be set depending on tank height.







TEDDINGTON KBB FIRE VALVES KBB Fire Safety Valve Why take the risk with anything else? The KBB fire valve is designed as a fire safety shut-off valve for use on oil burning equipment. The valve is installed in the oil supply pipeline outside the building with the sensor mounted firmly inside the

65°c FIRE VALVE

appliance above the burner.

OU UTITLE VALVE	
KBB/65/1.5	1.5m
KBB/65/3	3.0m
KBB/65/6	6.0m
KBB/65/9	9.0m
KBB/65/12	12.0m
KBB/65/16	16.0m
KBB/65/20	20.0m

90°c FIRE VALVE

90 G FINE VALVE	
KBB/90/2	2.0m
KBB/90/3	3.0m
KBB/90/6	6.0m
KBB/90/9	9.0m
KBB/90/12	12.0m
KBB/90/16	16.0m
KBB/90/20	20.0m

Teddington Fire valves have 1/4" female connection ports.

FIRE VALVE TEST UNIT



No: **KBT1000**

- Integrated single compact unit
- · Adjustable temperature setting
- Simple controls
- 230V operation
- Light weight robust construction
- · Eliminates hot kettles of water
- Testing time approx 3 minutes
- 'Ready' indicator light
- Will test all types of fire valves
- Conforms to EN 60730-1:1995

The single unit test box is designed to eliminate the need for jugs of hot water to test the operation of the fire valve at initial installation or during regular servicing.

It provides a safe and simple solution to valve testing.

REMOTE ACTING FIRE VALVE - 7mm Phial

The use of remote sensing fire valves is covered by BS 5410: Part 1: 1997 which is referenced as a requirement in the Building Regulations and Standards.



66°c FIRE VALVE

BBRAF6615C	1.5m
BBRAF6630C	3.0m
BBRAF6660C	6.0m
BBRAF6690C	9.0m
BBRAF66150C	15.0m

90°c FIRE VALVE

BBRAF9015C	1.5m
BBRAF9030C	3.0m
BBRAF9060C	6.0m
BBRAF9090C	9.0m

These Fire valves have 3/8" female connection ports.

HAND WHEEL FIRE VALVE

3/8" or 10mm compression



SPARE WHEEL

Spare Hand Wheel for Fire Valve



No: 1401002

LEVER FIRE VALVE KIT

3/8" or 10mm compression

3/8" No: **1403000** 1/2" No: **1403007** 3/4" No: **1403014**



No: **1402000**

DEADWEIGHT FIREVALVE KIT ONLY

9 metre 72°

No: **1404015**





TANKMASTER

TANKMASTER BODY COMPLETE

Designed to fit steel or plastic oil heating storage tanks. Eliminates the need for a seperate gate valve, level gauge, filter and several pipe fittings.

- Dimensions -155mm x 80mm
- Sight Tube 4ft 6" or 6ft (sold seperate)
- Tank Connection 1/2" BSP
- Oil Level Valve Pull to read (self closing)
- Flow Rate Up to 36 litres/hour
- Oil Line Outlet 10mm compression
- Complies with BS799 Part 2

The filter should be replaced whenever the boiler is serviced and is not washable.

No: TM4790





4ft 6"



6ft No: TM4500

No: COM2024

UPVC SHIELD



TANK GAUGE ADAPTER 180mm



No: TM4545

FILTER ELEMENT



No: TM4547

SIGHT GAUGE TOP CAP



No: TM4660F No: COM2180

TANKMASTER



No: TM4155

BOWL BOLT & SEAL



No: TM4675/4390

ON/OFF HANDWHEEL



No: TM4310

FILTER BOWL BODY



No: TM4326

'0' RING SET

9 Piece



GREEN FLOAT



No: **TM4400** No: SG2000-P

TANK GAUGE



4ft 6" No: SG1550 6ft No: SG1552

CONTENTS GAUGE



4ft No: **D1600** 6ft No: **D1610**

TANK GAUGE ISOLATION VALVE



PVC CLEAR TUBE

30m Coils Also sold per metre



No: **PB5290** No: COM2080



LOCKABLE VENT CAP

2" (Fits most tanks) Locks with padlock.



No: **3006055**

PLASTIC VENT CAP

2" (Fits most tanks)



No: **1703104**

TANK WATER ABSORBER



489ml No: **3011022** 1.59L No: **3011023**

COPPER TUBE

10mm



10 metres No: **TUBE1010P** 25 metres No: **TUBE1025P**

COPPER TUBE INSERT

10mm



No: **TM4172**

LOCKABLE VENT CAP

2" (Fits most tanks) Locks with key.



No: 3006056

METAL VENT CAP

2" (Fits most tanks)



No: **3006052**

TOP OFF TANK VALVE

Draw oil from the top of the tank.



No: **TTV-01**

COATED COPPER TUBE

10mm



10 metres No: **TUBE1010C** 25 metres No: **TUBE1025C**

CASH ACME A31S PRV

Oil, Gas or Water 4PSi outlet (adjustable) 3/8" connections 1/4" for gauge

No: **3001002**





GOK SMARTBOX® TANK GAUGE

Wired tank gauge which displays tank level in %, litres or height (cm).



No: 1703200

COMPACT TANK ALARM

ATEX certified Float switch supplied. Battery operated



Steel Tank No: **3808053**Plastic Tank No: **3008052**

SINGLE FILL POINT CABINET

Fill Point Cabinet 2" Single Fill (Top Entry)



No: **1707000**

ANALOGUE OIL TANK CONTENTS GAUGE

Sends the oil level direct to your Smart phone. Daily/weekly/monthly



No: 1705005

SMS TANK ALERT

Sends the oil level direct to your Smart phone. Daily/weekly/monthly



No: **6800200**

FUEL TANK TRANSFER PUMP

100 litres/min



No: 3805050





OUF OIL LIFTERS

The OUF88 range of oil lifters should satisfy most domestic market requirements. Can be used to replace the no longer available BM346 lifter. Suction lift 8 litres @ 8 metres vertical and up to 25m horizontal pipe run on 8mm inside diameter pipe.

This lifter has a third port to be used for an overflow pipe which has to be returned to the tank.

If it is not possible to do so an IR leak detector driptray has to be used. (Sold Seperately)

Oil Lifters

OUF 3.5 ltr	6808000
OUF 12 ltr	6808010
IR Drip Tray (3.5 ltr)	6800232
IR Drip Tray (12 ltr)	6800233



PUMP TYPE	Suction Solenoid Pump
LIFTING HEIGHT (MAX.)	8 m. vertical (8 mm I.D. tube)
MAX. HORIZONTAL DISTANCE	100 m. horizontal (8 mm I.D. tube)
OUTLET FLOW RATING (8 mm I.D. tube)	8 l/hr at: 8 m vertical & 25 m horizontal 15 l/hr at: 5 m vertical & 25 m horizontal
INLET CONNECTION	3/8" F BSP
OUTLET CONNECTION	3/8" F BSP
OVERFLOW OUTLET CONNECTION	1/2" F BSP
POWER SUPPLY	AC 230V, 50Hz
POWER CONSUMPTION	50 W
RESERVOIR TOTAL CAPACITY	3,5 Litre (Max: 12 litres)
DIMENSIONS (W x D x H)	240 x 130 x 335 mm (Max: 350 x 225 x 345)
WEIGHT	3 kg (Max: 4 kg)
FUEL TYPE	Kerosene and Diesel Oil

If the oil lifter is being fitted externally, it must be installed inside a weather proof box.

Weather Proof Boxes

400x300x200mm	3005002
500x400x200mm	3005005
600x400x230mm	3005006
800x600x300mm	3005008





WATCHMAN TANK GAUGES



SENSIT GAUGE

If your tank is 'SENSiT Ready', all you need is to buy the SENSiT

Check if you have the orange sticker on your tank (as shown below). This means you should have the grey transmitter Watchman Sonic Advanced pre-installed on your tank.

If you do not have the orange sticker and the grey Watchman Sonic Advanced transmitter as mentioned above, the SENSiT USB receiver will not work on its own.

You will need to get the full SENSiT Smart WiFi tank level monitoring kit which contains of the SENSiT USB receiver and the grey transmitter Watchman Sonic Advanced.





WATCHMAN ANYWHERE

Full kit No: WASONICADVANCED

Monitor oil levels via smartphone.



Suitable for all current ultrasonic models. 3V



80.

No: WAANYWHERE

No: CR2430



COMPRESSION COUPLING



8mm No: YKK6108 10mm No: YKK61010

COMPRESSION TEE



8mm No: YKKCEL08 10mm No: YKKCEL10

COMPRESSION STOP END



8mm No: YKK8MMCOMPBLANK 10mm No: YKK10MMCOMPBLANK

COMPRESSION → **MALE COUPLING**



8mm No: YKKCTE08 10mm No: YKKCTE10

$COMPRESSION \rightarrow FEMALE COUPLING$



 $10\text{mm} \to 1/4$ " No: **YKK6121014** 10mm → 3/8" No: **YKK6121038** $8mm \rightarrow 1/4$ " No: **YKK611814**

 $8mm \rightarrow 3/8" \text{ No: } YKK611838$ $10\text{mm} \to 1/4$ " No: **YKK6111014**

 $10mm \rightarrow 3/8$ " No: YKK6111038 **COMPRESSION** \rightarrow **MALE ELBOW**

COMPRESSION → **FEMALE ELBOW**



 $10\text{mm} \rightarrow 1/4$ " No: YKKELBFE1014 10mm → 3/8" No: **YKKELBFE1038**

 $1/4" \rightarrow 1/8"$ No: **BFBSH1418**



OLIVE



6mm No: OLIVE6 8mm No: OLIVE8 10mm No: OLIVE10 15mm No: OLIVE15



FLARED STRAIGHT





FLARED ELBOW

10mm → 10mm No: 10mm → 1/4"male No: 10mm → 3/8"male No: 10mm Nut to Suit No:



BLACK IRON NIPPLE

1/4" No: IFBLNIP14 3/8" No: IFBLNIP38 1/2" No: IFBLNIP12 3/4" No: IFBLNIP34




BLACK IRON PLUG

1/4" No: YH14PLUG 3/8" No: YH38PLUG 1/2" No: YH12PLUG 3/4" No: YH34PLUG



BLACK IRON CAP





BLACK IRON SOCKET

1/4" No: YH14SOCKET 3/8" No: YH38SOCKET 1/2" No: YH12SOCKET 3/4" No: YH34SOCKET



BLACK IRON ELBOW

1/4" No: **252MTB** 3/8" No: **252MTC** 1/2" No: **252MTD** 3/4" No: **252MTE**



BLACK IRON REDUCING NIPPLE

 $3/8" \rightarrow 1/4"$ No: 420 86 906 $1/2" \rightarrow 1/4"$ No: 420 86 909 $1/2" \rightarrow 3/8"$ No: 420 86 912 $3/4" \rightarrow 1/2"$ No: 420 86 921



BLACK IRON TEE

1/4" No: **154MMB** 3/8" No: **154MMC** 1/2" No: **154MMD** 3/4" No: **154MME**



TUBE CUTTERS



No: **TL020** Cuts 6-22mm

No: TL031 Spare cutting wheel

67





BUNDED TANKS

Even where current regulations might permit the use of single skin tanks, the additional environmental protection offered through the use of Atlas Bunded Tanks is strongly recommended for any oil storage.

Guaranteed for 10 years this well respected range of tanks offers an excellent combination of shapes, capacities and features. With designs to suit all locations, from narrow width for domestic situations with limited space through to large capacity for commercial,



industrial and agricultural use, the Atlas range of bunded tanks has a proven track record for over 10 years. When you invest in Atlas you are buying strength, affordability and reliability - fully specified and approved. Tanks you can trust

ATLAS 1200 LPBA

Capacity 1200ltr Length 2000mm Width 1400mm Height 1000mm



No: 1200LPBA

ATLAS 1300 BHA

Capacity 1300ltr Length 1800mm Width 1300mm Height 1300mm



No: 1300BHA

ATLAS 1900 BHA

Capacity 1900ltr Length 2190mm Width 1540mm Height 1460mm



No: 1900BHA

ATLAS 1000 BSA SL

Capacity 1000ltr Length 1890mm Width 640mm Height 1440mm



ATLAS 1000 BSA

Capacity 1000ltr Length 2050mm Width 710mm Height 1515mm



No: 1000BSA

ATLAS 1225 BSA

Capacity 1225ltr Length 2100mm Width 860mm Height 1550mm



No: 1225BSA



EXOCET FUEL ADDITIVES

A specialist fuel additive designed to improve the burn quality of domestic kerosene when used in range-style cookers and/or where vaporising burners are being utilised.

Ideal for burners which continually 'coke' up or have fuel pipe blocks.

- Lowers char value
- Reduces build up of carbon deposits and soot
- Inhibits growth of deposits in fuel storage tanks
- Minimises the potential for fuel tank corrosion
- Increases the fuel shelf life
- Reduces service problems
- 1 Litre of additive treats 5000 litres of fuel (1:1000)

Exocet Cooker Exocet Boiler

200ml No: **X01482TA200** 200ml No: **X01410H0200** 1 Litre No: **X01482TA1** 1 Litre No: **X01410H01**



OIL METERS - MECHANICAL

• Suitable for heating oil, naphtha, diesel and petrol applications

- Volume display on roller counter, in litres
- For horizontal, vertical or inclined mounting
- Threaded or flanged connections
- Suitable for temperatures for up to 130°C



VZO4	4mm (1/8")	Flow Range 1 – 50 litres/hr
VZO8	8mm (1/4")	Flow Range 4 - 135 litres/hr
VZ015	15mm (1/2")	Flow Range 10 – 400 litres/hr
VZ020	20mm (3/4")	Flow Range 30 – 1000 litres/hr
VZ025	25mm (1")	Flow Range 75 – 2000 litres/hr
VZ040	40mm (1" 1/2)	Flow Range 225 – 6000 litres/hr
VZ050	50mm (2")	Flow Range 750 – 20,000 litres/hr
VZ04-RV	4mm (1/8") c/w pulse output	Flow Range 1 – 50 litres/hr
VZ08-RV	8mm (1/4") c/w pulse output	Flow Range 4 – 135 litres/hr
VZ015-RV	15mm (1/2") c/w pulse output	Flow Range 10 – 400 litres/hr

The Envirogreen Low NO_x Range from Firebird

Bolow St. Ah

Boiler Technology at its best



SINCE 1980

Firebird®
Central to Heating







BOILER CONTROL STAT

50-80°C



No: ACCOOOSTA

OVER HEAT STAT

87°C



POPULAR LIMIT STAT

110°C



No: ACCOOOLMT

OVER RUN STAT



No: ACCOOOOHS

RELAY TANK STAT

78°C For Combi



No: ACCOOORTS

EARLY ALERT STAT

No: ACCOOOORS

87°C



No: ACCOOCEAS

DUAL STAT

P5 Popular With pocket



No: ACCOODST

DUALSTAT D5

Heatpac



No: ACCOOOTHR STAT POCKETS

FROST STAT



No: ACCOOOFST

No: ACCCOMPKT No: ACC003PKT





MECHANICAL TIME CLOCK

Single Channel



MECHANICAL TIMER KIT

Standard efficiency boilers



No: ACCOOCLK

ELECTRONIC TIMER KIT

Condensing boilers



No: **ACCOOOTIM**

COMBI PCB BOARD



No: **ACCOOOETM**

RELAY 230V AC



No: ACCOOOPCB

RELAY BASE

11 Pin



No: ACCOOORLY

PRESSURE SWITCH



No: ACCOOOBAS

RDB DIGITAL CONTROL BOX

Fitted with Post Purge



No: ACCOOPSW

BOILER PROBE

White Thermistor



No: **ZE20035388**

FLOW SWITCH PROBE

Red Thermistor



No: ACCOOOWTP

No: ACCOOORTP





PLATE HEAT EXCHANGER



PLATE HEAT EXCHANGER



No: ACC025PHE

PLATE HEAT EXCHANGER WASHERS

Set of four



No: ACC031PHE

PRESSURE RELIEF VALVE



No: ACCOOPHW

FLOW SWITCH

Combi MK II



No: ACCCOMSRV

FLOW SWITCH COMPLETE

MK I Upgrade



No: **ACCCOMFSW**

CIRCULATING PUMP



No: ACCBRSFSW

No: ACC022PIV

BALL VALVE

PUMP ISOLATION VALVE

22mm



No: ACC130PMP

THERMOSTATIC MIXING VALVE



Post 19

22mm



Pre 19 No: **ACCCOMTMV**Post 19 No: **ACCCHBWMV**

No: ACC022VAL





EXPANSION VESSEL

14 Litre



No: ACC012PVL

EXPANSION VESSEL

18 Litre



No: ACC014PVL

EXPANSION VESSEL HOSE

1/2"F Elb x 3/4"F Str



No: ACC018PVL

FILLING LOOP

400mm



No: **ACCCOMHOS**

NON-RETURN CHECK VALVE

15mm



No: ACCOOOFLH

FILLING LOOP VALVE



No: ACCCOMDCV

AUTO AIR VENT



No: ACC015FCV

NYLON CHECK VALVE



No: ACCCOMAAV

PRESSURE GAUGE

Combi/System



No: **ACCCOMPRG**





CHECK VALVES



Male \rightarrow Male No: **ACC034MMC**Male \rightarrow Female No: **ACC034MFC**Female \rightarrow Male No: **ACC034FMC**

CONDENSATE PUMP KIT



No: ACCENVPNP

SMALL SNORKEL HOSE



No: ACCOOOSSH

CONDENSATE TRAP



No: ACCOOOTRP

MISCELLANEOUS PARTS





Description	No
Combustion Door Insulation 50/70/90	ACC090GSK
Combustion Door Insulation 120	ACC120GSK
Combustion Door Insulation 150	ACC150GSK
Combustion Door Insulation 200	ACC200GSK
Combustion Door Insulation 250	ACC250GSK
Combustion Door Insulation 310	ACC310GSK
Combustion Door Insulation C20/C26/C35 (No Graphite Required)	ACC000DDS
Combustion Door Insulation C44/C58	ACC044GSK
Combustion Door Insulation C73	ACC073GSK
Combustion Door Insulation C100	ACC100GSK
Graphite Board C44/C58	ACC044GRA
Graphite Board C73	ACC073GRA
Graphite Board C100	ACC100GRA
Heatpac Key	ACC000KEY
Heatpac Lock	ACC000LCK



CONTROL STAT



No: TH11010989

LIMIT STAT



No: TH11010988

DUALSTAT



No: TH11017262

MANUAL LIMIT STAT



No: **THMAN10077**

SECONDARY HEAT EXCHANGER SEAL

Suitable for condensing models 12/24, 24/30



No: TH40724446

Suitable for

EXPANSION VESSEL

No: TH40724445

10 Litre



Vessel No: TH23016525 Hose No: TH22222217

AIR SNORKEL HOSE

condensing models

12/20, 12/16, 16/25

COMBUSTION DOOR SEAL

Clips sold seperately



Wall Hung No: TH72818371 Floor Standing No: TH72811296

FLUE GASKET



PRESSURE GAUGE 1/4" Rear connection



No: THGAF075 No: TH20716591





BOILER CONTROL THERMOSTAT

Combi MKII, Multipass, Euroflame Vortex Models (pre Sept 15)



No: TPBS34

TEMPERATURE CONTROL KNOB

All models (pre Sept 15)



No: TPBS30

BOILER CONTROL THERMOSTAT

Vortex Models (post Sept 15)



No: VBS146

PRIMARY STORE STAT

Combi MKII



No: MPCBS25

DUAL THERMOSTAT

Euroflame Boilerhouse Multipass Boilerhouse



No: DSBH

OVER HEAT THERMOSTAT

Combi MKII, V3 Euroflame, Multipass Vortex Models (pre Sept 15)



No: TPBS33

TEMPERATURE CONTROL KNOBS

(post Sept 15)





VBS136

Combi models No: VBS136 Non-combi models No: VB\$135

OVERHEAT THERMOSTAT

Vortex Models (post Sept 15)



No: VBS147

FROST STAT

All external models



No: EFBS23

DUAL THERMOSTAT

Vortex Boilerhouse



No: DSBH03LC



CONTROL PANELS - SERIAL NUMBER & ADDRESS REQUIRED WHEN ORDERING

Description	No
Vortex Pro Combi Internal 21-26kW	MPCBS104
(Pre 24/10/14)	
Vortex Pro Combi Internal 36kW	MDODO404V
(Pre 24/10/14)	MPCBS104X
Vortex Pro Combi External	MPCBS105N
(Post 24/10/14)	MEGDSTUSIN
Vortex Pro Combi Internal	MPCBS114N
(Post 24/10/14)	WIF CDS I 14N
Vortex Eco External W/H non-system	MPCBS106
Vortex Eco External W/H system	MPCBS106X
Vertex Fee Internel W/H non evetem	MDCDC100
Vortex Eco Internal W/H non-system	MPCBS108
Vortex Eco Internal W/H system	MPCBS108X





MECHANICAL PROGRAMMER



DIGITAL PROGRAMMERS

Single Channel No: **ETKIT**

Twin Channel No: **EPKIT**



No: MTKIT

BOILER ROCKER SWITCH

On/Off External models



HEATING ROCKER SWITCH

On/Off Double Pole Neon



No: EFBS21

TEMPERATURE CONTROL PCB

Vortex Pro combi (post 08)



PCB only No: **MPCBS96**PCB & sensor No: **MPCBS54E**

No: **EFB\$19**

TEMPERATURE CONTROL PCB

Combi V3 Vortex Pro combi (pre 08)



PCB only No: MPCBS97X
PCB & sensor No: MPCBS54X





PRESSURE RELIEF VALVE 2.5BAR

Combi MKII Internal **Furoflame Internal** Multipass System



No: MPCBS28

PRESSURE RELIEF VALVE 2.5BAR

Combi V3 Internal Vortex Pro Combi Vortex Pro Internal Vortex Eco Wallhung



No: MPCBS50

PRESSURE RELIEF VALVE 2.5BAR

Combi MKII External Furoflame External



No: MPCBS47

PRESSURE RELIEF VALVE 2.5BAR

Combi V3 External Vortex Pro External Vortex Eco



No: MPCBS50X

WATER PRESSURE GAUGE

Combi MKII Internal Combi V3 Euroflame System Multipass Internal



No: MPCBS24

WATER PRESSURE GAUGE

Combi MKII External Multipass External Vortex Pro External Vortex Eco S/System



No: MPSS02

WATER PRESSURE GAUGE

All Vortex models



No: VBS09

CONDENSATE TRAP

Vortex Models



No: VBS02

MAG ONE SYSTEM CLEANER



Magnetic system filter

No: VM01

FILLING LOOP KIT

c/w Valves



No: MPCBS30



CIRCULATING PUMP



Pump No: VBS159 Hot water lead No: VBS126A

CIRCULAR FLOW SWITCH

Vortex Pro Combi 21-26kW 36kW (post 08)

No: MPCBS71X

AUTO AIR VENT

All models

No: MPCBS29

FIBRE WASHERS



15mm No: **MPCBS34S** 22mm No: MPCBS34M

Diverter Valve No: MPCBS34L

TURBULATORS



360mm No: **VBS05** 476mm No: **VBS03** Wallhung No: WBS01

LOW PRESSURE SWITCH

Combi V3 Vortex Pro Combi

No: MPCBS49X/A

SQUARE FLOW SWITCH

Vortex Pro Combi 36kW (pre 08)

No: MPCBS71NT

MANUAL AIR VENT 3/8"

Vortex Pro Combi



No: MPCBS68

FLOW RESTRICTOR

All combi models



No: MPCBS39

NEONS

Red No: MPCBS46 Amber No: **EFBS25** Green No: MPCBS45







EXPANSION VESSEL 8 LITRE



No: WBS07

EXPANSION VESSEL 10 LITRE

Euroflame 50/70, 70/90 & external. Vortex Pro 15-21kW & 15-26kW (pre 08)

No: MPCBS27

EXPANSION VESSEL 10 LITRE FLAT

Vortex Pro Combi 21kW (pre 14)



No: MPSS08

EXPANSION VESSEL 12 LITRE

Euroflame Int. 50/90, 90/120 Multipass 50/70, 70/90, 90/140 Vortex Pro Combi 26kW (pre 14) Combi MKII. V3 Vortex Eco, Pro 15-26kW (post 08)

No: MPSS01

EXPANSION VESSEL 12 LITRE FLAT

Vortex Pro 26-36kW



No: VBS06

EXPANSION VESSEL 14 LITRE

Vortex Pro Combi 36kW (pre 14)



No: MPCBS70

EXPANSION VESSEL 16 LITRE

Vortex Pro 36-46kW



No: VBS38

VESSEL FLEXI HOSES



Combi MKII, Multipass Sealed System

No: MPCBS31

Euroflame Sealed System, Multipass

No: MPSS04

Vortex Eco, Pro Combi 26-36kW (pre 14)

No: MPCBS79

Vortex Pro Combi (post 14)

No: **VBS125**

Vortex Pro Ext. 15-21kW, Pro Combi (pre 14)

No: VBS95

Vortex Pro Wallhung

No: WBS08

EXPANSION VESSEL 24 LITRE

Multipass 140/160. 160/200 Vortex Pro Combi (post 14)

No: VBS124






BAFFLES

Description	No
MARK II	
Combi 70 Full Set	EFBS30
Combi 90 Full Set	MPBS13
Combi 90 Bottom Baffles	MPBS13X
V3	
Combi 70 Full Set	EFBS30
Combi 90 Full Set	MPCBS51
Combi 90 Bottom Baffles	MPCBS51X
Combi Max Full Set	MPCBS52

MPCBS52X



EFBS30

VORTEX PRO

Combi Max Bottom Baffles

15-21kW/Combi 21 Full Set	VBS93
15-21kW/Combi 21 Bottom Baffles	VBS93B
15-26kW/Combi 26 Full Set	VBS01
15-26kW/Combi 26 Bottom Baffles	VBS11
26-46kW/Combi 36 Full Set	VBS36
26-46kW/Combi 36 Bottom Baffles	VBS10
46-58kW Full Set	VBS76
58-70kW Full Set	VBS77



VORTEX ECO

15-26kW Full Set	VBS96
15-26kW Bottom Baffle	VBS96A
26-35kW Full Set	VBS97
12-21kW Wallhung Full Set	WBS03
12-21kW Wallhung Bottom Baffle	WBS03A
Combi 26 XS (Pre 16) Full Set	VBS137
Combi 26 XS (Post 16) Full Set	VBS137A



EUROFLAME

50/90 & 70/90 Full Set (Post 94)	EFBS09
50/70 Full Set	EFBS30
90/120 Full Set	EFBS49



MULTIPASS

50/70 Full Set	MPBS12
50/70 Bottom Baffles	MPBS12X
70/90 Full Set	MPBS13
70/90 Bottom Baffles	MPBS13X
90/110 Full Set	MPBS14
90/140 & 110/140 Full Set	MPBS15
90/140 & 110/140 Bottom Baffles	MPBS15X
140/160 Full Set	MPBS28
160/200 Full Set	MPBS27







COMBUSTION ACCESS DOORS

Description	No
Euroflame 50/90, 70/90, 90/120	
Pre Nov 03	EFBS18
Post Nov 03	EFBS20
Combi 70 MKI, V3, Euroflame 50/70	
Pre Nov 03	EFBS18X
Post Nov 03	EFBS20X
Combi 90 MKII, V3	
Multipass 50/70, 50/90, 70/90	MPBS16
Multipass 90/110, 90/140	MPBS17
Multipass 140/200	MPBS17L
Vortex Pro Combi 21kW	MPCBS111A
Vortex Pro Combi 26kW	02011111
Pre Dec 14	MPCBS110
Post Dec 14	MPCBS110A
Vortex Pro Combi 36kW	VBS69Z
Vortex Eco 15/26kW	VBS92
Vortex Pro 15/21kW	12002
Pre Nov 15	VBS94
Post Nov 15	VBS94A
Vortex Pro 15/26kW	
Vortex Eco 26/35kW	VBS69
Vortex Pro 26/46kW	VBS69X
Vortex Pro 46/70kW	VBS04
Vortex Eco W/H 12/21kW	WBS04
VOITON LOO VV/II IZ/Z II(VV	115007







VBS92

COMBUSTION DOOR SEALS

Description	No
Combi 90 MKII	
Combi 90 V3	TPBS23L
Multipass 50/90 & 90/140	
Multipass 140/200	TPBS24
Vortex Pro Combi 26kW	
Vortex Pro 15-26kW	VBS15
Vortex Eco 15-26kW	
Vortex Pro Combi 36kW	
Vortex Pro 26-46kW	VBS16
Vortex Eco 26-35kW	
Vortex Pro 46-70kW	VBS111
Vortex Eco Wallhung 12-21kW	WBS05





COMBI DIVERTER VALVE

Combi MKII Combi V3



DIAPHRAM KIT FOR DIVERTER VALVE

Combi MKII Combi V3



No: MPCBS33/A

COMBI MICROSWITCH

Combi MKII Combi V3



THERMOSTATIC MIXING VALVE

Combi MKII, V3 Vortex Pro Combi



No: MPCBS22F

No: MPCBS41

15 PLATE HEAT EXCHANGER

Combi MKII





No: MPCBS21/A

35 PLATE HEAT EXCHANGER

Vortex Pro Combi Combi V3



No: MPCBS53/A

ORANGE RELAY

Vortex Pro Combi External (pre 08)



ORANGE RELAY BASE

Vortex Pro Combi External (pre 08)



No: MPCBS75

No: MPCBS72X

Vortex Pro Combi



CLEAR RELAY

(pre 08)



CLEAR RELAY BASE

Vortex Pro Combi (pre 08)



No: MPCBS72B





OUALITY DESIGN. BUILT-IN RELIABILITY.



TANK & BOILER CONTROL STAT



Stat No: WA2131 Knob No: WA2166

BOILER LIMIT STAT Combi Models





No: WA281

SECONDARY HEAT EXCHANGER GASKET



No: WA2126

Non-Combi models



No: WA3009

CONDENSATE TRAP



No: WAWDS2

LOW PRESSURE SWITCH



No: WA3780

PLATE HEAT EXCHANGER



AUTO AIR VENT

No: WA3529

Complete with check valve



No: WA599 No: WA614



OUALITY DESIGN. BUILT-IN RELIABILITY.



No: WA2132

FILLING LOOP



No: WA2133

PRESSURE GAUGE



No: WA3019

MIXER VALVE



No: WA1621

PCB CONTROLLER





No: WA2419

PRESSURE VESSEL 12 LITRE



Hose No: WA2058

COMBI 90 120 TOP BAFFLE

290 x 275mm



No: WA015R-TOP

COMBI 90 120 MIDDLE BAFFLE

290 x 275mm



No: WA015R-MID

BAFFLE SET

380 x 408mm 22mm Holes

COMBI 90 120 BOTTOM BAFFLE

290 x 275mm



No: WA013R





BOILER CONTROL STAT



No: TR206896

BOILER CONTROL KNOB



No: TR206897

DHW CONTROL STAT



No: TR209850

BOILER LIMIT STAT



No: TR206892

TANK STAT



No: TR208096

BLOCKED FLUE STAT





No: TR208151

No: TR45651





No: TR221351

CLEANOUT DOOR SEAL (STRIP)



CLEANOUT DOOR SEAL (ROLL)





No: TR208151ROLL







PRESSURE RELIEF VALVE

1/2" 3bar



No: TR208078

DIVERTER VALVE



No: **TR208069**

DIVERTER VALVE REPAIR KIT



No: **TR222787**

HYDRAULIC REPAIR KIT



No: **TR222787/KIT**



No: TR222786

EXPANSION VESSEL



No: TR208651

VESSEL HOSE





No: TR207291

COTTON REEL IGNITOR



No: TR207292

AIR CONVEYOR



No: **TR20202** No: **TR221349**





BAFFLES



Pre April 2003		Part No	No. Required
50/65	TOP	TR221651	1
	BOTTOM	TR221650	5
70/90	TOP	TR208838	3
	BOTTOM	TR208834	1
100/125	TOP	TR208866/A	2
	BOTTOM	TR208871/A	6
130/150	TOP	TR209293	1
	BOTTOM	TR209290	4
160/180	TOP	TR209287	2
	BOTTOM	TR209288	8
170/250	ALL THE SAME	TR203278	9

April 2003 Onwards

50/90	TOP	TR208834	1
	BOTTOM	TR208838	3
100/125	TOP	TR208866/A	2
	BOTTOM	TR208871/A	6
130/240	TOP	TR209282	2
	BOTTOM	TR209280	8



worcester official stockist

The spares you need, when you need them.

We are a Gold Level Stockist with the top 200+ core parts stocked here.





PJ BURNER GASKET



OIL HOSE KIT



No: 87161409020

ISO BULKHEAD VALVE 1/4"



No: 87161153110

ISO BULKHEAD VALVE 1/4"

Straight



No: 87161424230

PRESSURE RELIEF VALVE



No: **8716119692**

PRESSURE GAUGE 1/8"

Fits Heatslave



No: 87161424160

HEATSLAVE DIVERTER ACTUATOR



No: 87161423580

HEATSLAVE DIVERTER VALVE BODY



No: 87161049200

DIVERTER VALVE CARTRIDGE



No: **87161049190**

HEATSLAVE FLOW SWITCH

Complete assembly



No: 87161051320

No: 87161200690



HEATSLAVE PLATE HEAT EXCHANGER



No: 87161429060

AUTO AIR VENT 3/8"



No: 87161405000

HEATSLAVE PCB



No: 87161463010

HEATSLAVE RECTANGULAR VESSEL



Vessel No: 87161425050 Hose No: 87161405070

PROGRAMMER HIGHFLOW 400







No: 77161920070

No: 87161423100

DANESMOOR POST PURGE UNIT



HEATSLAVE GREEN CONTROL KNOB



No: 87161463080 No: 87161410870

HOT WATER STAT



Heatslave

BOILER CONTROL STAT



No: 87161423130 No: 87161423090

www.abgo.co.uk





GREENSTAR DIVERTER ACTUATOR

GREENSTAR DIVERTER VALVE BODY

Drayton



No: 87161087230

Pre 2009

GREENSTAR DIVERTER VALVE BODY

Post 2009



No: 87186822900

CAMRAY FLOW SWITCH



No: 87161087220

CAMRAY ACTUATORS

HSA3CD

No: **87161083990**

HSA3ND

No: 87161110860





No: 7716190050

PUMP VALVE 22mm - 1 & 1/2"



No: 87161424170

GREENSTAR HEATSLAVE PCB



No: 87186852610

HEATSLAVE DIVERTER VALVE

V4044



No: 87161201310

HEATSLAVE WATER ISO VALVE



No: 87161424180



GREENSTAR HEATSLAVE VESSEL

12 litre



No: 87161076600

GREENSTAR VESSEL HOSE



No: 87161124260

ROUND VESSEL

12 litre



No: 87161083890

GREENSTAR FLOW SWITCH



No: 87161114060

CONTROL STAT

Camray BBEL00230



No: 87161078720

GREENSTAR PROGRAMMER



No: 7716192033

LIMIT STAT

Camray BBFI 00215



No: 87161078710

ABGO are profile stockists for Worcester oil and gas heating spares.

Please have the boiler serial number to hand for part matching.



worcester

official

stockist



Grandee

CONTROL STAT



No: GB10016

HIGH LIMIT STAT



No: GB10017

EXPANSION VESSEL 10LTR





EXPANSION VESSEL 10LTR

Winkelmann Same end connections

No: GB10003

PLATE HEAT EXCHANGER



8" No: **GB10028A** 12" No: **GB10028S**

FLOW SWITCH



No: GB10001

PRESSURE RELIEF VALVE



No: GB10011

FROST STAT



No: **GB10018**

MIXER VALVE

No: **GB10000**



PRESSURE GAUGE



No: GB10012

SOLLESTON

BOILER CONTROL STAT



BOILER LIMIT STAT

Statesman 110°C



No: 26009018

No: **26009097**

EXPANSION VESSEL



Hose

No: **26009158**

PLATE HEAT EXCHANGER

Statesman



No: **26009107**

FLOW SWITCH





DIVERTER VALVE ASSEMBLY

Statesman



No: 26009166

PRESSURE/TEMPERATURE GAUGE

Statesman

MIXER VALVE

No: 26009160

Statesman



No: **26009159**

CONTROL KNOB

Statesman



INTEGRATED TIME SWITCH

Statesman

No: 26009148



No: **26002014**

No: **10/19114**





WALLSTAR CONTROL STAT



Condensing No: EL023A Non-Condensing No: EL023

LIMIT STAT

110°C



No: **EL220**

COMBI EXPANSION VESSEL





NON RETURN VALVE

1/4"



No: **SYS010**

COMPLETE MANIFOLD ASSEMBLY



No: COM012

No: BSUFK-3

WALLSTAR DIVERTER VALVE KIT

Heating Side



Diverter Kit No: COM423 Diaphragm Kit No: COM424

MICRO SWITCH ASSEMBLY



No: **EL040**

WALLSTAR MIXER VALVE

Complete with pipes



No: **COM011**

OIL LINE & FILTER

PRESSURE RELIEF VALVE



No: COM301 No: **BS099A**



BOILER CONTROL STAT



HIGH LIMIT STAT

Manual Reset



No: CK1568002

EXPANSION VESSEL



No: **CK1568004**

PLATE HEAT EXCHANGER

15-41kW



No: CC1541007

FLOW SWITCH



CONTROL KNOB & BEZEL



No: CC1568003

PRESSURE GAUGE



No: **CK1568001**

MIXER VALVE



No: CC1568007

PRESSURE RELIEF VALVE



Includes Bracket

CONDENSE TRAP

No: CC3065MIX



No: cc1568008

No: CTR005



The only oil boiler with a Which? Best Buy for the second year running.

#MustBeVortex

VORTEX PRO UTILITY RANGE

Tried & trusted Riello Low NOx burner technology

Awarded the coveted Which? Best Buy for the second year running

Internal & external models with outputs from 15-70kW

Exceptional seasonal efficiency of up to 93.3%*

Also available in the Vortex Range:

VortexBlue Vortex Eco **Vortex Boiler House**





Which?

Oil Boilers September 2018



www.grantuk.com















GRANT OIL CONDENSING BOILERS

An award winning, tried and tested oil-fired boiler range

The name 'Grant' has in recent years become synonymous with highly efficient oil-fired central heating appliances. Designs like the 'Multi Pass' boiler achieved efficiency levels far in excess of any UK or European Standards and have helped thousands of homes to reduce their annual fuel bills. So it will come as no surprise to see Grant yet again leading the way with the Grant Vortex oil-fired condensing boiler range with exceptional SAP2009 efficiencies up to 93.3% gross (97% gross for SAP2005). Grant's ultra-high efficiency condensing oil boiler range has been on the market for over 15 years and now features 63 different model variations, with outputs ranging from 12 - 70kW (50.000 - 240.000 Btu/h).



Condensing boilers differ from traditional boilers in that they are designed to capture heat normally lost through the flue system during the combustion process. Unlike traditional oil-fired boilers the Grant Vortex condensing boiler has a built-in stainless steel heat exchanger incorporating Grant's unique turbulator baffle system, which cools the gases to a point where the latent heat, normally lost to the atmosphere through the flue, can be usefully extracted. The additional energy recovered enables the boiler to operate continuously at much higher efficiency levels, resulting in lower heating and hot water running costs.

Easy to commission, service and maintain

As with all oil-fired appliances, Grant Vortex Condensing Oil Boilers require commissioning at the time of installation. This simple process ensures that the boiler is working at peak efficiency which, in turn, will result in lower running costs and long term reliability. Annual maintenance is also made easy by Grant's cleverly designed front service access to both the burner and all the internal serviceable parts. This feature enables Grant Vortex Condensing Boilers to be fitted neatly and unobtrusively within either the kitchen or utility room environment. Alternatively, if internal siting is problem, space-saving outdoor versions are available.

The innovative VortexBlue Range

As part of its dedication to cleaner energy, Grant introduced the Grant VortexBlue range which combines its proven condensing boiler technology with a revolutionary new blue flame. Using a new state-of-the-art Riello Blue Flame compact burner alongside the familiar Vortex oil-fired-boiler, this market-leading combination gives you an easy to install, reliable product with those all-important low emissions.









VORTEX ECO UTILITY RANGE

The Grant Vortex Eco Utility range was launched as a direct response to customer demand for a competitively priced condensing boiler.

The Eco models incorporate the latest version of the Grant Vortex stainless steel heat exchanger. Out-puts range between 15kW and 35kW (50-120,000Btu/h) with SAP 2009 gross seasonal efficiencies of 90.3 - 90.8% gross.

As you would expect from a product with this pedigree, Grant Vortex Eco Utility boilers are exceptionally quiet in operation and feature the latest Riello burner technology. The boilers also have a simplified casing control panel and

boilers are exceptionally quiet in operation and feature the latest Riello burner technology. The boilers also have a simplified casing, control panel and pipework arrangement, making them the ideal choice for utility room installations. All standard Eco Utility boilers are designed to allow the burner and combustion chambers to be serviced from the front, however, models fitted with a sealed system kit require top service access.

with a sealed system kit require top service access.		
No Description		
VTXEC015/21	Vortex ECO Utility Internal 15/21 kW	
VTXEC021/26 Vortex ECO Utility Internal 21/26 kW		
VTXEC026/35 Vortex ECO Utility Internal 26/35 kW		



VORTEX ECO WALL HUNG RANGE

Available in outputs ranging from 12-21kW, in both sealed system and open-vented system variants, these new appliances are pre plumbed and encompass Grant's patented Vortex stainless steel heat exchanger and turbulator baffle system. All internal models require a separate flue kit (not supplied with the boiler) and are compatible with all Grant EZ-Fit low level, high level and vertical flue systems, so now almost any installation situation can be catered for

No	Description
VTXOMWH12/16	Vortex ECO External Wall Hung 12/16 kW
VTXOMWH16/21	Vortex ECO External Wall Hung 16/21 kW
VTXSOMWH12/16	Vortex ECO External System Wall Hung 12/16 kW
VTXSOMWH16/21	Vortex ECO External System Wall Hung 16/21 kW
VTXSWH12/16	Vortex ECO Internal System Wall Hung 12/16 kW
VTXSWH16/21	Vortex ECO Internal System Wall Hung 16/21 kW
VTXWH12/16	Vortex ECO Internal Wall Hung 12/16 kW
VTXWH16/21	Vortex ECO Internal Wall Hung 16/21 kW



VORTEX ECO OUTDOOR RANGE

Today, as around one in four oil boiler installations are external, Grant have expanded the number of options available with the launch of three competitively priced Eco External modules. The models have outputs between 15kW and 35kW (50-120,000Btu/h) and SAP 2009 gross seasonal efficiencies of 90.3 - 90.8% gross. Grant's wall hung oil-fired boiler range comprises four internal and four external models.

No	Description
VTXOMECO15/21	Vortex ECO External 15/21 kW
VTXOMECO21/26	Vortex ECO External 21/26 kW
VTXOMECO26/35	Vortex ECO External 26/35 kW







VORTEX PRO OUTDOOR RANGE

All Pro External modules enjoy the same unique features as the Eco External modules including the factory fitted multi-directional flue, high quality external powder coated casing, built in frost protection, mains isolating switch and a test switch.

However, in addition, the boilers have a higher efficiency level and are factory wired to receive an 'optional' RF (radio frequency) wireless programmer. In this situation, the receiver can be plugged into the control panel of the module, enabling the boiler to be operated using a remote controller from any room inside the house, without the need for hard wiring.

No	Description
VTX0M15/21	Vortex PRO Outdoor 15/21 kW
VTXOM15/26	Vortex PRO Outdoor 15/26 kW
VTXOM26/36	Vortex PRO Outdoor 26/36 kW
VTXOM36/46	Vortex PRO Outdoor 36/46 kW
VTXOM46/58	Vortex PRO Outdoor 46/58 kW
VTXOM58/70	Vortex PRO Outdoor 58/70 kW



VORTEX PRO BOILER HOUSE RANGE

The new Grant Vortex Boiler House models come in a distinctive powder coated casing in our iconic Grant red and feature an externally mounted Riello RDB burner and dual thermostat.

They have high energy efficiency ratings which not only significantly lower fuel bills but also considerably reduce greenhouse gas emissions and lessen the environmental impact of domestic hot water and heating systems.

The Grant boiler House models are ideal for locations that are difficult to access like cellars or plant rooms, where a white cased utility version is not always the best solution. The Boiler House models encompass the same unique stainless steel heat exchangers used in other Vortex boilers together with Grant's exclusive turbulator baffle system which provides ultra-high efficiency and low running costs. These additions to the Vortex range are compatible with all Grant EZ-Fit Flue systems and are flued in exactly the same way as Utility models, further enhancing installation options.

No	Description
VTXBH15/21	Vortex PRO Boiler House 15/21 kW
VTXBH21/26	Vortex PRO Boiler House 21/26 kW
VTXBH26/35	Vortex PRO Boiler House 26/35 kW
VTXBH36/46	Vortex PRO Boiler House 36/46 kW
VTXBH46/58	Vortex PRO Boiler House 46/58 kW
VTXBH58/70	Vortex PRO Boiler House 58/70 kW





VORTEX PRO KITCHEN UTILITY RANGE

The Grant Vortex Pro Kitchen/Utility range has been upgraded to enable a number of new programmer options to be used with the appliance. A plug-in programmer (Product code: EPKIT) can be installed within the fascia, or alternatively, the receiver for Grant's new wireless RFT Kit (Product code: RFTKIT) can be located within the knockout and the programmer sited conveniently within the building. The boilers have very high SAP 2009 gross seasonal efficiencies of between 90.7 - 93.3% and feature the 'award winning' unique Grant Vortex stainless steel condensing heat exchanger, and turbulator baffle system. The 15-21 utility model has been designed to fit within a kitchen unit and, due to its reduced width, can be used as a direct replacement for most older oil-fired boilers.

		0.	1
1	14		i I
	1		
g	B		
			Ш
	(Ш
		1 :	ľ

No	Description
VTX15/21	Vortex PRO Kitchen/Utility 15/21 kW
VTX15/26	Vortex PRO Kitchen/Utility 15/26 kW
VTX26/36	Vortex PRO Kitchen/Utility 26/36 kW
VTX36/46	Vortex PRO Kitchen/Utility 36/46 kW
VTX46/58	Vortex PRO Kitchen/Utility 46/58 kW
VTX58/70	Vortex PRO Kitchen/Utility 58/70 kW
VTXS15/26	Vortex PRO Kitchen/Utility System 15/26 kW
VTXS26/36	Vortex PRO Kitchen/Utility System 26/36 kW
VTXS36/46	Vortex PRO Kitchen/Utility System 36/46 kW

VORTEX PRO COMBI RANGE

Grant Vortex Pro Combi features much larger heat exchangers which, due to their low water content and larger surface area, vastly increase the hot water performance available and mixing valves are pre-set at 50°C, controlling accurately the hot water draw off temperature from the boiler. They also feature a low system pressure cut off switch, enabling the combi to protect itself in the unlikely event of system water loss. Additionally, there are two very accurate electronic temperature controls which allow the boiler to operate in condensing mode on central heating, whilst maintaining its instant hot water production.

No	Description
VTXCOMBI21	Vortex PRO Internal Combi 21 kW
VTXCOMBI26	Vortex PRO Internal Combi 26 kW
VTXCOMBI36	Vortex PRO Internal Combi 36 kW
VTXOMCOMBI21	Vortex PRO External Combi 21 kW
VTXOMCOMBI26	Vortex PRO External Combi 26 kW
VTXOMCOMBI36	Vortex PRO External Combi 36 kW









VORTEXBLUE INTERNAL RANGE

The Grant VortexBlue combines our proven condensing boiler technology with a revolutionary new blue flame. Using a new state-of-the-art Riello Blue Flame compact burner alongside the familiar Vortex oil-fired boiler, this market-leading combination gives you an easy to install, reliable product with those all-important low emissions. The Grant VortexBlue internal models combine our existing proven condensing boiler technology with the latest Riello RDB BLU compact burner. The boilers feature a sleek white casing, unique control panel with neon diagnostic indicators and simplified pipework arrangement, making them the ideal choice for utility room installations.

No	Description
VTXBF21	VortexBlue Internal 15/21 kW
VTXBF26	VortexBlue Internal 21/26 kW
VTXBF36	VortexBlue Internal 26/36 kW
VTXSBF21	VortexBlue Internal Sealed System 15/21 kW
VTXSBF26	VortexBlue Internal Sealed System 21/26 kW
VTXSBF36	VortexBlue Internal Sealed System 26/36 kW



VORTEXBLUE COMBI RANGE

The intelligent VortexBlue Combi incorporates the latest Riello RDB BLU burner technology and combines it with our award winning Vortex stainless steel heat exchanger. The Grant VortexBlue Combi features large heat exchangers which, due to their low water content and larger surface area, vastly increased the hot water performance. With a low system pressure cut off switch, the combi protects itself in the unlikely event of system water loss.

No	Description
VTXBFCOMBI21	VortexBlue Combi 21 kW
VTXBFCOMBI26	VortexBlue Combi 26 kW
VTXBFCOMBI36	VortexBlue Combi 36 kW
VTXSBFOMCOM21	VortexBlue Internal Sealed System 15/21 kW
VTXSBFOMCOM26	VortexBlue Internal Sealed System 21/26 kW
VTXSBFOMCOM36	VortexBlue Internal Sealed System 26/36 kW



VORTEXBLUE EXTERNAL RANGE

The Grant VortexBlue external modules have some of the highest oil-fired boiler

efficiencies available today. These models are ideal for situations where a white cased kitchen/utility version is not always the best solution, possible due to limited space within the home.

All modules include a factory fitted multi-directional flue, high quality external powder coated casing, built in frost protection, mains isolating switch and a test switch. Just as other VortexBlue boilers, this range also incorporates Riello's RDB Blu burner technology teamed with our patented Vortex stainless steel heat exchanger.

No	Description				
VTXBFOM21	VortexBlue External 15/21 kW				
VTXBFOM26	VortexBlue External 21/26 kW				
VTXBFOM36	VortexBlue External 26/36 kW				





Join this growing network of heating engineers and benefit from the wide range of opportunities this installer scheme has to offer.

- Extended product guarantees of up to 10 years
- Exclusive access to G1 Portal and G1 Click app
- Company profile on Grant UK website

Full Terms & Conditions apply for Scheme membership and extended guarantees

www.grantuk.com







INTERNAL HEAT ONLY BOILERS

- Low NOx and Blue Flame options available
- Compact design fits under standard kitchen worktop (outputs up to 35kW)
- Fully insulated and acoustically designed for ultra-quiet operation
- PCB controller using highly accurate thermistors with anti-cycling function (outputs up to 35kW)*
- Front service access
- Multi-directional flue options
- High performance Low NOx and Blue Flame burners complete with full diagnostic control box



Envirogreen	No.	Output	Efficiency	Weight
Kitchen 12-18	EGE018KIT	12-18kW	95.2 %	115 kg
Kitchen C20	EGE020KIT	20kW	94.8 %	125 kg
Kitchen C26	EGE026KIT	26kW	94.8 %	128 kg
Kitchen C35	EGE035KIT	35kW	94.4 %	131 kg
Kitchen C44	EGE044KIT	44kW	93.6 %	210 kg
Kitchen C58	EGE058KIT	58kW	92.7 %	216 kg
Kitchen C73	EGE073KIT	73kW	92.0 %	242 kg
Commercial Utility C100	EGE100KIT	100kW	n/a	390 kg

Envirolite	No.	Output	Efficiency	Weight
Utility CR20	EGE020UTL	12-20kW	93.8 %	125 kg
Utility CR26	EGE026UTL	20-26kW	93.7 %	128 kg
Utility CR35	EGE035UTL	26-35kW	92.9 %	131 kg

EXTERNAL HEAT ONLY BOILERS

- Low NOx and Blue Flame options available
- Compact design fits under standard kitchen worktop (outputs up to 35kW)
- Fully insulated and acoustically designed for ultra-quiet operation
- PCB controller using highly accurate thermistors with anti-cycling function (outputs up to 35kW)*
- Front service access
- Multi-directional flue options
- High performance Low NOx and Blue Flame burners complete with full diagnostic control box











Envirogreen	No.	Output	Efficiency	Weight
Heatpac 12-18kW	EGE018HPK	12-18kW	95.2 %	134 kg
Heatpac C20	EGE020HPK	20kW	94.8 %	154 kg
Heatpac C26	EGE026HPK	26kW	94.8 %	154 kg
Heatpac C35	EGE035HPK	35kW	94.4 %	158 kg
Heatpac C44	EGE044HPK	44kW	93.6 %	244 kg
Heatpac C58	EGE058HPK	58kW	92.7 %	250 kg
Heatpac C73	EGE073HPK	73kW	92.0 %	280 kg
Envirogreen	No.	Output	Efficiency	Weight
Envirogreen Slimline Heatpac C20	No.	Output 20kW	Efficiency 93.0 %	Weight 147 kg
	1	<u> </u>	,	<u> </u>
Slimline Heatpac C20	TBC	20kW	93.0 %	147 kg
Slimline Heatpac C20 Slimline Heatpac C26	TBC TBC	20kW 26kW	93.0 %	147 kg 150 kg
Slimline Heatpac C20 Slimline Heatpac C26 Slimline Heatpac C35	TBC TBC TBC	20kW 26kW 5kW	93.0 % 93.0 % 92.0 %	147 kg 150 kg 153 kg
Slimline Heatpac C20 Slimline Heatpac C26 Slimline Heatpac C35 Envirolite	TBC TBC TBC No.	20kW 26kW 5kW	93.0 % 93.0 % 92.0 % Efficiency	147 kg 150 kg 153 kg Weight

BOILERHOUSE REGULAR BOILERS

- Low NOx and Blue Flame options available
- Constructed using premium quality steel
- Fully insulated casing minimises heat loss
- PCB controller using highly accurate thermistors with anti-cycling function (outputs up to 35kW)*
- Multiple tapping points for ease of installation
- Patented heat exchanger design
- Multi-directional flue options
- High performance Low NOx and Blue Flame burners complete with full diagnostic control box
- Models available in outputs of 12kW to 100kW







modele dramable in outpate t			- 3	
Envirolite	No.	Output	Efficiency	Weight
Boilerhouse CR20	EGE020SBH	20kW	93.8 %	107 kg
Boilerhouse CR26	EGE026SBH	26kW	93.7 %	112 kg
Boilerhouse CR35	EGE035SBH	35kW	92.9 %	115 kg





Envirogreen	No.	Output	Efficiency	Weight
Popular 12-18kW	EGE018POP	12-18kW	95.2 %	99 kg
Popular C20	EGE020POP	20kW	94.8 %	107 kg
Popular C26	EGE026POP	26kW	94.8 %	112 kg
Popular C35	EGE035POP	35kW	94.4 %	115 kg
Popular C44	EGE044POP	44kW	93.6 %	182 kg
Popular C58	EGE058POP	58kW	92.7 %	190 kg
Popular C73	EGE073POP	73kW	92.0 %	210 kg
Popular C100	EGE100POP	100kW	n/a	300 kg

INTERNAL SYSTEM BOILERS

- Low NOx and Blue Flame options available
- Compact design fits under standard kitchen worktop (outputs up to 35kW)
- Fully insulated and acoustically designed for ultra-quiet operation
- PCB controller using highly accurate thermistors with anti-cycling function (outputs up to 35kW)
- Factory-fitted expansion vessel and circulating pump
- Multi-directional flue options
- High performance Low NOx and Blue Flame burners complete with full diagnostic control box



Envirogreen	No.	Output	Efficiency	Weight
System C20	ESE020DLX	20kW	94.8 %	143 kg
System C26	ESE026DLX	26kW	94.8 %	146 kg
System C35	ESE035DLX	35kW	94.4 %	149 kg
System C44	ESE044DLX	44kW	93.6 %	235 kg

EXTERNAL SYSTEM BOILERS

Envirogreen	No.	Output	Efficiency	Weight
Systempac C20	ESE020NKT	20kW	94.8 %	163 kg
Systempac C26	ESE026NKT	26kW	94.8 %	163 kg
Systempac C35	ESE035NKT	35kW	94.4 %	166 kg
Systempac C44	ESE044NKT	44kW	93.6 %	270 kg
Slimline Systempac C20	ESE020SLM	20kW	93.0 %	147 kg
Slimline Systempac C26	ESE026SLM	26kW	93.0 %	150 kg
Slimline Systempac C35	ESE035SLM	35kW	92.0 %	153 kg



INTERNAL COMBI BOILERS

- Low NOx and Blue Flame options available
- Excellent hot water performance
- · Rapid reheat after hot water draw-off
- Standard and Slimline models
- Fully insulated and acoustically designed for ultra-quiet operation
- Durable casings with a high-quality finish
- PCB controller using highly accurate thermistors
- Front service access
- Multi-directional flue options
- High performance Low NOx and Blue Flame burners complete with full diagnostic control box



-					
Envirogreen	No.	Output	DHW Flow	Efficiency	Weight
Combi HE C20	ECE020DLX	20kW	16 ltr/min	93.0 %	167 kg
Combi HE C26	ECE026DLX	26kW	16 ltr/min	93.0 %	170 kg
Combi HE C35	ECE035DLX	35kW	20 ltr/min	93.0 %	173 kg
Slimline Combi C20	ECE020SLM	20kW	12-14 ltr/min	92.5 %	165 kg
Slimline Combi C26	ECE026SLM	26kW	16 ltr/min	92.5 %	168 kg
Slimline Combi C35	ECE035SLM	35kW	16 ltr/min	91.0 %	172 kg

EXTERNAL COMBI BOILERS

The Firebird ranges of external Combi Boilers are similar in specification to their equivalent internal models, with the addition of a built-in frost thermostat

There is no requirement to house the boiler in a building, so this option provides an ideal solution if internal space is at a premium.

The boilers have removable sides for ease of access to any part of the unit.

Piping can be carried out from the back or from underneath











Envirogreen	No.	Output	DHW Flow	Efficiency	Weight
Combipac HE C20	ECE020CPK	20kW	16 ltr/min	92.0 %	200 kg
Combipac HE C26	ECE026CPK	26kW	16 ltr/min	92.0 %	200 kg
Combipac HE C35	ECE035CPK	35kW	20 ltr/min	91.6 %	203 kg



FRANCO BELGE





OIL STOVES, THE SMART OPTION

- Clever -They look and feel like a wood burning stove but without the work involved cutting logs and their storage. An oil tank is all you need.
- Clean No carrying wood into the house and ash out with all the resulting mess that can cause. No unexpected wildlife taking up residence in your home.
- At over 75% efficiency they can cost as little as £2.04 per day to run (Belfort - based on 50p per litre).
 They require no electricity to run. Once lit
- the gravity oil flow will keep it burning, so even in a power cut you are guaranteed a warm room in your home.

 Open the door to the room and let the stove heat a greater area. They come as standard with Franco Belge's unique ignition

system allowing simple, no mess, lighting.



 Designed to provide a continuous source of background heating with the ability to increase the heat output at the turn of a dial. The result is less temperature variation, which minimises cold draughts, and because

- it never has to heat the house from cold a smaller heat output is required from the stove than would be required from a cycling system or wood burning stove to heat a similar area.
- Low maintenance. The Franco Belge vaporising burner pot burns so efficiently that carbon deposits are kept to a minimum. The operation of a simple de-coking rod on the inlet for the oil into the burner is all that is required during the heating season. Like all heating appliances a yearly service by an OFTEC engineer is required.
- Peace of mind. ABGO's experienced technical team are available to answer any questions you may have. Spare parts are not an issue either and with nearly 50 years of supplying the heating industry throughout the UK you will never be let down.



BELFORT

No.	FB1740506
H/W/D	558 / 420 / 530mm
Weight	68kg
Flue Outlet ID (Top or Rear)	100mm / 4"
Efficiency	80%
Nominal Heat Output	5kW
Fuel Type	Oil



SAVOY

Fuel Type	Oil
Nominal Heat Output	8kW
Efficiency	80%
Flue Outlet ID (Top or Rear)	125mm / 5"
Weight	100kg
H/W/D	660 / 535 / 554mm
No.	FB1740707



BURGUNDY

No	FR1741059
H/W/D	760 / 620 / 544mm
Weight	118kg
Flue Outlet ID (Top or Rear)	125mm / 5"
Efficiency	81%
Nominal Heat Output	10kW
Fuel Type	Oil



OPTIONAL COAL OR LOG EFFECT KITS

Type of Effect	No.
Log Effect	FB10922
Coal Effect	FBCE103






SALES COUNTER NOW OPEN

PART MATCHING FOR ALL GAS BOILERS, FIRES, COOKERS, HEATERS AND CYLINDERS!





Unit 1 Sidings Close
Wolverhampton WV11 3DR
Open weekdays 7:30 - 5:30pm
Saturdays 8:00 - 12:00pm (Winter Only)



Heating Controls



22mm Motorized 3 Port Valves

22mm Motorized 2 Port Zone Valves

Full Programmers 7day 5/2day 24hr

Full Timeswitches 7day 5/2day 24hr

Wireless Programmable Room Stat Packs

Wireless Room Stats

Programmable 5/2day Room Stats

DANFOSS





HP22 087N660900



FP715Si 087N789800



TS715Si 087N789900



2-1

RETBRF & RX1 087N727600



TP5000Si 087N791000

DRAYTON





ZA5/679-2





LP111 LP711



RF700 Digistat Plus2RF RF701 Digistat Plus3RF



Digistat Plus Room Stat



22084 Digistat Plus 22083 Digistat Plus

SIEMENS HONEYWELL SUNVIC V4073A1039 CMV322 SDV2211 V4043H1056 CZV222 SZV2212 ST9400C1000 RWB29Si ST9500C1015 RWB2007 SunPro2000 ST9100A1008 RWB27Si ST9100C1006 SunPro1000 RWB1007 CMT721D1019 RDJ10RF **TLXRFPV** CMT921A1042 REV24RF SunStatRF DT92E TLX1010 TLX1012 Y6630D1007 RDH10RF

SunStat

REV24RF

CMT701A1014 CMT907A1041



Drayton

POTTERION

HONEYWELL SYNCHRON MOTOR

240V



DRAYTON SYNCHRON MOTOR

240V



No: 40002737003/U

UNIVERSAL SYNCHRON MOTOR

240V



No: **28670**

HONEYWELL BALL & PLATE



No: **SYNCHRON** No: **40003918007/U**

ELECTRONIC TIME SWITCH

EP1 Electronic Timeswitch - Replacement for older EP4000, EP4002, EP5002 Models

- Potterton EP1 Single Channel Timeswitch
- Up to Three on/off periods per day.
- Digital Clock Display.
- Independent 7 day programming.
- Fully pumped and gravity heating systems.
- Battery backup in the event of power failure.
- Dimensions: 104x161x49 HxWxD
- Common Base Plate To EP Range.

No: 7211472

AOV EXT

ELECTRONIC PROGRAMMER - 2 CHANNEL

EP2 Electronic Programmer - Replacement for older EP2000, EP2001, EP2002, EP3002, EP6002 Models

- Potterton EP2 Twin Channel Programmer for controlling Central Heating & Hot Water.
- Suits both fully pumped and gravity heating systems.
- Digital Clock Display.
- Up to Three on/off periods per day.
- LED Curcuit Indicators.
- Independent control of heating or hot water.
- Common Base Plate To EP Range of Programmers
- Clock Maintained During Power Failure
- Dimensions: 104x161x49mm HxWxD

No: 7211473







The one to fit, where others don't.

The new MagnaClean Atom is a super compact, space saving filter, developed to provide effective magnetic filtration in the tightest of installation spaces.

The slip socket designs allows for installation in just under two minutes and with horizontal servicing 115mm is the total space required.


















MagnaClean[®]

Small space. Big idea.

www.adev.com/atom

THE GAME **CHANGER**

MagnaClean

Professional 3 Sense

DEFINING THE FUTURE OF WATER TREATMENT

www.adey.com/pro3



THE FILTER THAT CONNECTS DIRECTLY TO YOUR SMARTPHONE ALLOWING VISIBILITY OF YOUR CUSTOMERS HEATING SYSTEMS.



Drayton Wiser



Start with your room thermostat for central smart control

Then add radiator thermostats

Continue to add radiator thermostats in each room

Smart rooms with Wiser

Wiser can offer complete home personalisation by allowing you to control the temperature and schedule in each room independently.

It makes ultimate comfort affordable. Start with a smart room thermostat and build a full multi-room system over time.

This simple upgrade can have a huge impact on your comfort, convenience and energy bills.

- Smart heating & hot water control
- User friendly smartphone app
- Individual room control
- Eco Mode to maximise savings
- Works with Amazon Alexa









No: WT714R9K0902

THREE CHANNEL THERMOSTAT KIT



No: WT734R9K0902

SMART MULTI-ZONE THERMOSTAT KIT 1



No: WV714R9K0902

ROOM THERMOSTAT



No: WN704R0S0902



No: WT724R9K0902

SMART PLUG



No: WB704H1A0902

SMART MULTI-ZONE THERMOSTAT KIT 2



No: WV724R9K0902

SMART RADIATOR TRV



No: WV704R0A0902



Honeywell





T6 SMART THERMOSTAT

Touch-screen interface.

Location features determine when your home is vacant or when you are on your way home adjusting the temperature automatically.

Features a choice of schedule settings to fit your lifestyle, including 7 day, 5/2 day and single day scheduling with up to 6 different time settings per day.

T6 Wired No: **Y6H910WF1011** Decor Plate No: **ACC400**

T6R Wireless No: Y6H910RW4022



C1 Wi-Fi SECURITY CAMERA

Live stream of your home in wide-angle 720p HD with 5x digital zoom & night vision.

Get rapid notifications and clips of any unusual activity sent to your smart device.

No: HAWCIC1S



See the bigger picture in 1080P HD with 145° wide-angle view and 6x digital zoom.

The camera turns off and on automatically, depending on your location (geofencing)

No: **HAWCIC2S**





Honeywell

19"

D-m

Honeywell





EVOHOME

Wireless and expandable zoning thermostat for your home.

Touch-screen interface.

Learns exactly how long your property takes to heat up. The right temperature in the right place at the right time.

Use your mobile to monitor and control your heating anytime from anywhere.

Upgrading your basic thermostat control to

evohome smart zoning could save you up to 40% on your annual energy bills.

Designed for gas, fuel, wood and electric boilers. Heat-pump. Zone valve.

Radiators or under floor heating when zoning.

Simply connect it to your Wi-Fi network and download the app from the Apple store or Google play store.

Starter Pack No: ATP921R3100 Hot Water Kit No: ATF500DHW

MULTIZONE TRV KIT



MULTIZONE TRV



No: HR924UK No: HR92UK





- Three constant curves/constant speed curves
- Two proportional-pressure curves
- Two constant-pressure curves
- Low EEI (Energy Efficiency Index)
- Deblocking device
- Alarm and warning indication
- · Low noise level

Built on a platform proven in millions of boilers, the new UPS3 combines increased energy efficiency, an easier to wire plug and on board diagnostics with stalwart features such as ceramic bearings and shafts, a manual

deblocking port and robust start-up functionality.

Plus, clever design means the new UPS3 can be used not only in system installations but also inside many of the UK's domestic boilers. Simply scan the old pump with the new Grundfos GO Replace smartphone app and it will tell you if the UPS3 is a compatible fit. That gives you the chance to fix even integrated pump issues in one visit, saving you time and your customer money.

No: 99199622

PUMP VALVES

PFEXT25	Water Pump Extension 25mm
PFEXT45	Water Pump Extension 45mm

PFGATE22	Water Pump Gate Valve 22mm
PFGATE28	Water Pump Gate Valve 28mm

PFNUT	•
PFWASHER F	Replacement Washer





Tools & Consumables





ABZORB SPILLAGE KIT

Perfect kit for cleaning up oil spills upto 25 litres.

- Abzorb oil eater
- 1 metre absorbent snake
- 250ml bottle of Abxtract cleaner
- Gloves, safety goggles and Supazorb wipes

No: A06-0006

SWEET AIR SPRAY

Oil Neutraliser Cherry scented CFC free



ENVIRONMENTAL OIL CLEANER

For all those oil spills and stains



No: C04-60-200

No: C04-60-520

Just leave it near the



CHERRY BOMB

boiler or in your van to remove oil odours



PURE AIR

Suitable for turning all nasty smells into pure air



No: C04-60-225

ODOUR ELIMINATOR SPRAY

Heavy Duty Neutralizer



No: C04-60-215

SWEET AIR POWDER

For instant deodorization leaving a pleasant cherry smell



No: C04-60-620

SOOT REMOVER

Place into the combustion chamber to remove all soot and tar effortlessly

No: C04-35-515

EOGB WATER DETECTING PASTE

A simple method to check for water in the oil tank



No: C04-60-406



FUEL SPILL SPONGE

Soaks up oil by turning into a rubber mat.

Bio-degradable

No: C04-60-205



'SUCK-IT' ABSORBENT MAT

Absorbs water, oil & other liquids



No: **S07-0002**

ENGINEERS SERVICE MAT

Water, dirt & oil resistant. Place under boilers or radiators.

No: RFG-M38

DUSTSHEET

Extra Heavy 12ft x 9ft



No: DUSTSHEET

ENGINEERS GENERAL SPILL KIT 9L

Soaks up oil & water. Contains 5 pads, 1 cushion & bag tie



No: 3011008

KIMBERLY CLARK PAPER TOWELS

2x Ply Paper Roll 10" Steel Blue



No: KIMWIPE

Heavy duty wipes to remove oil & grease



AMBERSIL TOUGH WIPES

No: TOUGHWIPE

REGIN HAND WIPES

Highly absorbent duel sided textured wipes



No: REG-W50

ULTRA GRIME WIPES

100 Pack



No: UGWIPES

RE-USEABLE OVERSHOES

Size 10 No: 3010950 Size 10% No: 3010951

Size 11 No: **3010952** Size 11% No: 3010953

Size 12 No: 3010954





LATEX GLOVES



No: **GLN703** - Medium No: **GLN704** - Large No: **GLN705** - Extra Large

EBONY NITRILE GLOVES

Pack of 100

No: **EB702** - Small No: **EB703** - Medium No: **EB704** - Large No: **EB705** - Extra Large

3 PIECE FLUE BRUSH KIT

1" x 500mm 2" x 500mm 3" x 900mm

No: REG-T56

3 PIECE FLUE BRUSH KIT

5/8" x 500mm Round 2" x 500mm Flat 2" x 500mm Round

No: REG-T55

HENRY VACUUM CLEANER

"HENRY" Vacuum with Cable Rewind, including A1 Kit

Standard No: HVR200-M Metal No: NQS-250-21-AS1

BLACK MAMBA GLOVES

Pack of 100

No: **3010992** - Medium No: **3010993** - Large No: **3010994** - Extra Large

SWARFEGA HAND CLEANER

500ml

Swarfega

No: **DETUF500**

5" & 12" Handles 2x 12" Extensions 50mm Round Head (L) 50mm Round Head (S) 50mm Flat Head

7 PIECE FLUE BRUSH KIT

No: **REG-T51**

BOA BRUSH

24" Long Handle6" Long Head2" Diameter

No: 595012

VAC BAGS

No: **604015-1CH** No: **604016-2BH**

No: **604017-3B** No: **604019-4B**

No: 604020-5B



CLOSURE PLATE TAPE

50m Roll Black



ALUMINIUM FOIL TAPE

45m Roll 45mm Wide



No: REG-J75

BROWN OIL TAPE

33m Roll



No: REG-J70 **PTFE TAPE**

12 Metre Roll



No. RFG-A07

GAS TAP GREASE

Molycote



No: PTFE

SILICONE GREASE

50g WRC Approved



No: **REG-Z15**

DUAL X BOILER CLEANER

The most advanced safe and effective chemical cleaning technology available in today's market for Oil Boiler Cleaning and servicing.

Dualx saves time and effort, on average this cleaning agent could save a servicing engineer about 6 hours in a normal working week.

Condensing and non-Condensing Oil Fired Boiler Cleaning Agent.

Twin Pack Powder & Spray









LD90 LEAK DETECTION SPRAY

400 ml



No: **1930**

AC90 MAINTENANCE SPRAY

425 ml



No: 2006

SPRAY ADHESIVE

500ml



No: AMBERNC500

ROCOL OIL SEAL

300g

Thixotropic hard setting for pressure tight seals.



STAG "B" JOINTING PASTE

500g Tin



OILSEAL

No: REDB500

LEAK DETECTION GEL

250 ml



AIR DUSTER

150 ml



No: REG-Z05

REGIN WATER DETECTING PASTE

Water Finding Paste

for Oil - 3oz



No: **REG-003**

BRIGON CO² FLUID

Red



No: **BG2603003-1**

HELDITE JOINTING COMPOUND

250mm C/W Brush

No: HELD250

500g Paste

No: HELD-CAN500



HEATBOND FIXING COMPOUND

Stove Rope Fixative 125ml Bottle



No: HY201610

CERAMIC ROPE

Available in braided or soft. From 6mm to 25mm



No: CERROPE

STOVE ROPE ADHESIVE

Heat Resistant 850°c 30ml Bottle



No: REG-Y25

HIGH TEMPERATURE SEALANT

White No: REG-Z35 Clear No: REG-Z36 Black No: REG-Z37



CERAMIC BOARD (1M2)



10mm No: CERABOARD10 20mm No: CERABOARD20

FIRE CEMENT



2Kg No: CG602122B



2Kg No: CG602122

5Kg No: CG602123



FLUE 'N' FIRE SEAL

Silicate Cement 150ml Heat Resistant 1500°c



No: **REG-732**

SMOKE PELLETS





Pack of 10 REG-S15 Tub of 100 REG-S20

SMOKE MATCHES

12 per box (approx)



No: REG-S05

BOILER CLEANER


EXPEL "C" Boiler Cleaning Chemical

No: 2199998









RAPID DOSE	使用于安	
Description	COUNTY COURSE OF PERSONS ASSESSMENT	No
X100 Rapid Dose 400ml	HAN WOOD WOOD WOOD	X100RD
X200 Rapid Dose 400ml	ATOU ALOU AND	X200RD
X400 Rapid Dose 400ml		X400RD
Rapid Dose Leak Sealer		RD-LS
Rapid Dose filling loop adaptor		RD-FLA
Rapid Dose radiator adaptor		RD-RA
Rapid Dose tool kit		RD-TK



500ML CHEMICAL RANGE		
Description	Ellesteron Ellesteron	No
Protector F1	Systems 11 Section 12	56599
Boiler noise silencer F2	TATE TO SEE	56602
Cleaner F3	**************************************	56600
Leak sealer F4		56603
RAPID DOSE		
Description	FILE POLICE	No
Protector F1 Express, 265ml		58229
Boiler noise silencer F2 Express, 265ml		58231
Leak sealer F4 Express, 265ml	283 283	58232
Cleaner F5 Express, 280ml		58230



MAGNACLEAN PROFESSIONAL 2

2 Year Manufacturer's Guarantee

22mm No: CP1-03-00022-01

28m No: FL1-03-01357



MAGNACLEAN TWIN TECH



No: FL1-03-01274

FERNOX TF1 FILTER



GRANT MAG ONE

No: MCTT001



22mm No: 59256 28mm No: 59257

No: GTVM01

ADEY CHEMICAL RANGE

				# 10m		
Description		(8)		(B)	INCS	No
MC1 Protector 500ml	English	-	The state of		Carrier I	CH1-03-01669
MC2 Silencer 500ml	the same	Ann d	America.	2000		CP1-03-00994
MC3 Cleaner 500ml		_				CH1-03-01670
MC4 Leak Sealer 500ml						CP1-03-00998
MC5 Rapid Flush 500ml						CP1-03-00999

ADEY RAPIDE

-	THE RES CO. LEWIS CO., LANSING MICH.	
Description	MEAN TO VIEW THE TEST	No
MC1 Rapide Dose 300ml	THE PARTY OF THE P	CH1-03-01640
MC2 Rapide Dose 300ml		CH1-03-02038
MC3 Rapide Dose 300ml	Test State S	CH1-03-01645
MC4 Rapide Dose 300ml		CH1-03-02039
MC10 Rapide Dose 300ml		CH1-03-02040



FireAngel®



WIRELESS INTERLINK SMOKE ALARM & THERMOPTEK MULTI-SENSOR SMOKE ALARM

WST-630T



- technology
- Large central button Test / Smart Silence / Locate
- Locate feature
- Smart Silence
- Sleep Easy



Wi-Safe 2

ST-622T

- Thermoptek Multi-Sensor technology
- · 10 year sealed for life lithium battery
- Large central button
- Easy installation
- Smart Silence
- Sleep Easy
- Used and endorsed by UK Fire and Rescue Services

WIRELESS CLASS A1 HEAT ALARM AND CLASS A1 HEAT ALARM

WHT-630T



- · 10 year sealed for life lithium battery
- Large central button Test / Smart Silence / Locate
- Locate function
- Smart Silence





HT-630T



- Thermistek technology, incorporating a unique radiant heat dish
- · Class A1 heat alarm
- · 10 year sealed for life lithium battery
- Large central button Test / Smart Silence
- Smart Silence

7 YEAR CO ALARM

CO-9XT-FF



- · Advanced electrochemical sensor calibrated and tested in CO gas
- 7 year sealed for life lithium battery
- · Alarm can be free-standing or wall mounted
- Supplied with tamper resistant Fast-Fit bracket with single pin or 2 screw fitting options
- · Test button and LED status indicators

COLD ALARM

CDA-9X



Cold alarm provides an early warning before the room temperature falls to a dangerously low level.

- · Easy to install
- Completely portable
- A series of visual and audible warnings when the temperature drops
- Large easy press test and silence button
- Sealed alarm with internal power pack lasting 10 years

10 YEAR CO ALARM

CO-9X-10T-FF



- · Advanced electrochemical sensor calibrated and tested in CO gas
- · 10 year sealed for life lithium battery
- · Alarm can be free-standing or wall mounted • Supplied with tamper resistant Fast-Fit bracket with single pin or 2 screw fitting options
- Test button and LED status indicators

REPLACEABLE BATTERY CO ALARM

CO-9D



- Test/Reset button for weekly alarm testing
- Powered by 2 x AA alkaline batteries
- 7 year warranty
- BŚ EN 50291:2001

DURACELL

PLUS POWER













Description	Per Pack	No
AA SIZE	4	DCAAX4
AAA SIZE	4	DCAAAX4
C SIZE	2	DCCX2
D SIZE	2	DCDX2
9V SIZE	1	DC9VX1

WORKMATE TORCH

Handheld torch c/w 6V Battery (Replacement battery EC009)



TORCH BATTERY

6 Volt



No: **EC011**

ENGINEERS ELECTRIC LEAD LIGHT

5 metre cable & 13A plug fitted to both

240 volt

No: **010816113**

110 volt

No: **010816123**



VOLT SENSOR

No: EC009

Regin



No: REG-T15

CONNECTOR BLOCKS



5 amp No: **EC5CON** 15 amp No: **EC15CON**

240V FUSES

Pack of 10

3 amp No: **EC007** 5 amp No: **EC006** 13 amp No: **EC005**





OIL PRESSURE GAUGE 300PSI

0-300 PSI. 1/8" BSP General Purpose 20 Bar



No: 1703001

PRESSURE GAUGE TEST TEE

Oil Pump Testing Tee 1/8 inch



No: 1703000

PRESSURE GAUGE EXTENSION

1/8" BSP 80mm long



No: 3008876

OIL SUCTION PUMP

Used to prime oil lines



Pump No: 3006035

Replacement Seal Kit No: 3006036

OIL PRESSURE GAUGE 300PSI

0-300 PSI 1/8" BSP Glycerine Filled. High Accuracy 20 bar



No: 1704001

HIGH PRESSURE GAUGE HOSE

Used to connect Gauge to Test Tee

No: **FOL100**

OIL PRESSURE TEST KIT

C/W Case, 2x gauges, test tee, H.P hose, & connecting nipples



OIL MEASURING CYLINDER

Pyrex 50ml Glass Measuring Cylinder

No: CYG030030





For installing Vapourising Burner/Range Cookers

- Bi-Directional Spirit Level
- Pyrex Measuring Cylinder
- Steel Rule

Supplied in foam cased plastic carry case



ABGO

OIL EXTRACTOR UNIT

2.7ltr Vessel

Ideal for emptying drip trays, tank cabinets, bunds or sucking up fuel spills.

Can be used to prime oil lines.
Can also be used with water.

No: 3008100



OIL TANK WATER EXTRACTOR UNIT

6ltr Vessel Bi-directional (Pump or Suction)



GOK OIL LINE PRESSURE TEST KIT

Hand Pump Pressure gauge to 6 bar Includes connecting hose & carry case.

No: **3006037**



Kane Smoke Pump Papers and case included



BRIGON SMOKE PAPERS

Pack of 40 Smoke Papers



No: **BG2602008**

DRAUGHT GAUGE



No: **BG2601003**

FAN PULLER



No: **REG-T25**

FLARING TOOL

Metric Standard 45 Degree (4.75 - 10mm)

No: **REG-0100**

THERMOCOUPLE TESTER

Regin



No: REG-T20





WIND-UP HEAD TORCH

3x LED



WIND-UP TORCH

3x LED



No: 40407

TRIMMING KNIFE

Easy Find Retractable



No: 42989

5 METRE MEASURING TAPE

5m/16ft Value Soft Grip Metric/Imperial



No: **75285**

30 PIECE HEXAGONAL KEY SET

30 piece Metric/Imperial Combined Long Pattern Hexagon Key Set



No: **09229**

HEXAGONAL KEY TOOL

8 piece Metric Hexagon Key Tool/Set



No: **36000**

8 PIECE SCREWDRIVER SET

8x Piece Cabinet Pattern Screwdriver Set



No: **73070**

4 PIECE VDE SCREWDRIVER SET

4x Piece VDE Approved Fully Insulated



No: 14077

7 PIECE VDE SCREWDRIVER SET

7x Piece VDE Approved Fully insulated c/w Mains Tester



No: **07495**

11 PIECE SCREWDRIVER SET

11x Piece VDE Approved Fully Insulated



No: 07496

MOLEGRIPS SET

3x Piece Curved Jaw Self grip pliers



No: 14040

KNIPEX WATER PUMP PLIERS

Fully Insulated 250mm Alligator - Water Pump Pliers



No: 32013

ADJUSTABLE WRENCH SET

3x Piece Soft Grip Adjustable Wrench Set

No: **88598**

3 PIECE VDE PLIERS SET

3x Piece **VDE** Approved Fully Insulated Slimline Pliers Set

No: 49157



4x Piece 200mm Soft Grip Engineers File Set



No: 44962

12 PIECE SPANNER SET

12x Piece **Expert Hi-Torque** Metric Combination Spanner Set

No: 64605



5 to 26 Compartment Organiser

No: 73508

TOOLBOX / ORGANISER

Toolbox with tote tray



No: 11497

TOOL BOX



Large Tool Box

No: 27732

DIGITAL MULTIMETER

Protective case, Battery Included

No: 60792









Kit Options	Analyser, flue probe, batteries, manual, calibration report	Infra-red printer, (KMIRP)	Carry case	NiMH rechargeable batteries and charger	KANE MSP Smoke Pump	0-300psi pressure gauge & pressure gauge manifold	Compound gauge (pressure and vacuum)	High pressure hose & 2 x adaptors
KANE250	·							
KANE250 Kit	·	1	1	√				
KANE250 Oil Kit	·	1	1	4	1	~	4	√

Low annual service costs and 5 year extended warranty when serviced annually by Kane

Kane International reserves the right to make changes to products & specifications without prior notice. E & OE. ® The KANE logo is a registered trademark of Kane International Ltd



709R Kit Options

TPI 709R Flue Gas Analyser Kit

Combustion Efficiency Analyser:
 Measure O₂, CO, and flue temperature.
 Calculate efficiency, excess air, CO₂
 & (CO/CO₂) Ratio.

CO Analyser:

Measure carbon monoxide in ambient air.

Differential Manometer:

 +/- 150 mBar
 (0.01 mBar resolution)

 Great for Tightness/Let By or Burner Pressure Testing

Differential Thermometer:
 Dual input K-Type
 thermocouple thermometer
 measures differential
 temperatures


Ideal for Measuring & Recording
Flow & Return Temperatures



Kit options available

Kit 1 add a TPI A740 IR Printer













Kit 1 OIL add an IR Printer, Smoke Pump & Oil Filter





SPRINT PRO MODELS & KIT OPTIONS Pro1 Pro1 Kit Pro2 Pro2 KitA Pro2 KitB Pro3 Pro3 KitA **Pro3 KitB** Sprint Pro4,5 & 6 analysers and kits supplied with accessories as shown in Pro3 images above



SPRINT PRO ACCESSORIES & SPARES



All prices exclude VAT & carriage charges where applicable



www.abgo.co.uk



Follow us on Social Media

ABGO

Unit 1 Sidings Close, Wednesfield Road, Bentley Bridge Business Park, Wolverhampton WV11 3DR

Tel: (01902) 790 900 Fax: (01902) 790 909 Text: 07917 772582 Email: sales@abgo.co.uk



Edition OB4.3