

# OIL UP FEEDER

## OUF-88 & OUF-88 Maxi

# OUF-88



<b>PUMP TYPE</b>	Suction Solenoid Pump
<b>LIFTING HEIGHT (MAX.)</b>	8 m. vertical (8 mm I.D. tube)
<b>MÁX. HORIZONTAL DISTANCE</b>	100 m. horizontal (8 mm I.D.. tube)
<b>OUTLET FLOW RATING (8 mm I.D. tube)</b>	8 l/hr at: 8 m vertical & 25 m horizontal 15 l/hr at: 5 m vertical & 25 m horizontal
<b>INLET CONNECTION</b>	3/8" F BSP
<b>OUTLET CONNECTION</b>	3/8" F BSP
<b>OVERFLOW OUTLET CONNECTION</b>	1/2" F BSP
<b>POWER SUPPLY</b>	AC 230V, 50Hz
<b>POWER CONSUMPTION</b>	50 W
<b>RESERVOIR TOTAL CAPACITY</b>	3,5 Litre (Maxi: 12 litres)
<b>DIMENSIONS (W x D x H)</b>	240 x 130 x 335 mm (Maxi: 350 x 225 x 345)
<b>WEIGHT</b>	3 kg (Maxi: 4 kg)
<b>FUEL TYPE</b>	Kerosene & Diesel Oil



### Optional Fittings

- Leak Detection Kit & 245 mm Tray for OUF-88
- Leak Detection Kit & 350 mm Tray for OUF-88 Maxi

### Product code

6800232  
6800233

